

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 013688

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Atlantic

9. WELL NO.

4 (OWMO)

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC. T., R., M., OR BLK. AND

SURVEY OR AREA

Sec. 25, T-31-N, R-10-W

N.M.P.M.

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

Box 990, Farmington, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

1595'S, 890'W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6384' RL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 10-13-66 pulled tubing because of junk in hole, set cement retainer at 4655', squeezed open hole w/325 sacks cement. Found hole in 7" casing at 1950'. Set cement retainer at 1834', squeezed hole w/150 sacks cement. Found hole in 7" casing (184 - 214'), circulated thru bradenhead, cemented w/75 sacks cement. W.O.C. 12 hours, tested casing O. K.

On 10-18-66 Total depth 5772'. Ran 180 joints 4 1/2", 10.5#, J-55 casing (5762') set at 5772' w/125 sacks cement. W.O.C. 18 hours, tested w/3800#/30 Min. OK

On 10-19-66 Perf Lower Point Lookout 5555-63', 5635-43', 5655-63', 5690-98' w/2 SPF frac w/50,000# 20.40 sand, 50,000 gallons of water. Max. pr. 4000#, BDP 4000#, tr. pr. 1900-2600-3000#. I.R. 45 BPM. Dropped 3 sets of 16 balls each, flushed w/4050 gal. water. ISIP 0. Set bridge plug at 5543', tested w/4000# O. K. Perf. Upper Point Lookout 5426-38', 5472-84', 5501-13', 5521-27' w/24 SPZ. Frac w/50,000# 20/40 sand, 57,890 gallons of water. Max. pr. 4000#, BDP 1800#, tr. pr. 2000-3350-4000#. I.R. 36 BPM. Dropped 3 sets of 24 balls each, flushed w/2400 gallons of water. ISIP 0. Set bridge plug at 4936', tested w/4000# O. K. Perf. Cliff House 4898-4908, 4918-28' w/2 SPF; frac w/30000 # 40/60 sand, 28,730 gallons of water. Max. pr. 4000#, BDP 2600#, tr. pr. 2200-2400-2800#. I.R. 51 BPM. Dropped 1 set of 20 balls, flushed w/3310 gallons of water. ISIP 150#, 5 Min. 0.

18. I hereby certify that the foregoing is true and correct

SIGNED Original Signed F. H. WOOD

TITLE

Petroleum Engineer

DATE 10-20-66

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

OCT 26 1966
OIL CON. COM.
DIST. 3

RECEIVED

OCT 25 1966

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-355229

807-0 51

