

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Federal <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator El Paso Natural Gas Company 3. Address of Operator Box 990, Farmington, New Mexico 4. Location of Well UNIT LETTER H , 1650 FEET FROM THE North LINE AND 990 FEET FROM THE East LINE. SECTION 27 TOWNSHIP 31N RANGE 10W NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 6250' GL	7. Unit Agreement Name 8. Farm or Lease Name Atlantic A 9. Well No. 1-A 10. Field and Pool, or Wildcat Blanco Mesa Verde 12. County San Juan
---	--

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

OTHER **Case, Cement, and fracture treat** ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

To increase production it is intended to workover and recompleat this well in the following manner:

Squeeze cement the 7" annulus at the top of the Fruitland formation (2575').

Clean out the old hole or whipstock and redrill through the Mesa Verde formation to approximately 5350'.

Run full string of 4 1/2" production casing and run cement to tie into the bottom of the 7" casing.

Perforate and sand-water frac the Mesa Verde formation.

In the event it is necessary to whipstock, squeeze cement the open hole through a retainer, set near the bottom of the 7" casing with approximately 250 sacks of cement.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original signed by

SIGNED Carl E. Matthews

TITLE Petroleum Engineer

DATE 5-27-65

APPROVED BY Emery Clume

TITLE Supervisor Dist. # 3

DATE 6-1-65

CONDITIONS OF APPROVAL, IF ANY:

