X

(SUBMIT IN TRIPLICATE)

Lease No. 078463-A

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

NOTICE OF INTENTION TO DRILL	NOTICES AND REPORTS ON WELLS
NOTICE OF INTENTION TO CHANGE	SURSFORENZ
TOTICE OF INTENTION TO THEY WAS	SURSEQUENT POR
I TO BE DOWN	SUBSPONENT DEPART
The state of the s	The state of the s
INTENTION TO PULL OF	SUBSPOLLENT DEPAR
NOTICE OF INTENTION TO ABANDON WELL	SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY
	HISTORY IV
(INDICATE AR	OVE DV
	SOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	OR OTHER DATA)
Hale-Adobe	Kabena a 2 a
Well No. 1-29	450 ft. from ${N \atop g}$ line and 1450 ft. from ${E \atop m}$ line of sec. 28
is located 1	450 ft. from Nine 1
NE 28	mie and 1450 ft. from line of see 22
(% Sec. and Sec. No.)	31 N 13 W NM: M (Range)
Dakasa Dakasa	(Range)
(Field)	(County or Subdivision) (Meridian)
he also at	above sea level is 5674 ft. KB
ing	DETAILS OF WORK re sands; show sizes, weights, and lengths of property
12-10-90	DETAILS OF WORK re sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- s points, and all other important proposed work)
Drilled ta account	re sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- points, and all other important proposed work) 35'. Ran 9 5/8" 32# H-#0 casing to 193'. Cemente 2% HA-5. Plug down 5:00 a.m. Tested to 600 SI
Drilled ta account	re sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- g points, and all other important proposed work)
Drilled 13 3/4' hole to 1 with 200 ax cement with and held CK.	re sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-reports, and all other important proposed work) 35'. Ran 9 5/8" 32# H-#0 casing to 193'. Cemente 2% HA-5. Plug down 5:00 a.m. Tested to 600 usq
Drilled 13 3/4' hole to 1 with 200 ax cement with and held CK.	re sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-reports, and all other important proposed work) 35'. Ran 9 5/8" 32# H-#0 casing to 193'. Cemente 2% HA-5. Plug down 5:00 a.m. Tested to 600 usq
Drilled 13 3/4' hole to I with 200 ax cement with and held CK. Inderstand that this plan of work must receive pany Consolidated Cil &	re sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-reports, and all other important proposed work) 35'. Ran 9 5/8" 32# H-#0 casing to 193'. Cemente 2% HA-5. Plug down 5:00 a.m. Tested to 600 usq
Drilled 13 3/4' hole to 1 with 200 ax cement with and held CK.	re sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-reports, and all other important proposed work) 35'. Ran 9 5/8" 32# H-#0 casing to 193'. Cemente 2% HA-5. Plug down 5:00 a.m. Tested to 600 usq