

0			

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. NM 01614
Unit Thompson

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	XX
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 10, 1962

Thompson
Well No. 6-D is located 1055 ft. from N line and 1080 ft. from W line of sec. 28

NW 1/4 Section 28
(1/4 Sec. and Sec. No.)

T-31N
(Twp.)

R-12W
(Range)

N.M.P.M.
(Meridian)

Basin Dakota
(Field)

San Juan
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 6076 ft. G.L.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

P.B.T.D.- 7170 '
Sand-water froed with 52,600 gals. water, 50,000# sand, 2% acid
Breakdown pr.- 2500
Avg. treating pr.- 1900
Avg. I.R.- 20.2 bpm
Max. pr.- 2500
Dropped 9% rubber ball sealers, flushed with 150 Hbls.
Injected with 305,600 SCF Nitrogen at 230 SCF per Hbl.
Instant shut in-1400
Ran 219 jts., 6943' of 2 3/8" tubing, landed at 6953
Shut in for gauge.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Antec Oil and Gas Company

Address Drawer # 570

Farmington, N.M.

By ORIGINAL SIGNED BY JOE C. SALMON
Joe C. Salmon

Title District Superintendent