	Fori (A	n 9-3 pril 19	331 b (52)	
į		; ; ;		X
i			!	

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agenc Navaje Tribel
Allottee
No.14-20-603-2037

## SUNDRY NOTICES AND REPORTS ON WELLS

SE NE/4 Sec. 25  SIN 17W NMPM  (4 Sec. and Sec. No.)  Horseshoe Gellup Ext.  Sen jusn  (County or Subdivision)  (County or Subdivision)  The elevation of the derrick floor above sea level is 5774  The elevation of the derrick floor above sea level is 5774  DETAILS OF WORK  (State names of and expected depths to objective and all other important proposed work)  2-6-59 Total Depth 1562'.  Ran 40 joints, 11-1/2", 15.500, 1-55 Casing (1550') set at 1560' with 50 secks regular cement, 50 secks Fozmin, 4% Gel., 1/40 Flocele per seck.  Held 10000/30 Minutes.  Top of cement by temperature survey at 670'.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  El Paso Nistural Gas Products Company  Past Office Soy 1565	NOTICE OF INTENTION TO CHANGE PLANS	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF. NOTICE OF INTENTION TO REDRILL OR REPAIR WELL. NOTICE OF INTENTION TO SHOULD OR ACIDEZ. NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO PROPOSED ALTER CASING. NOTICE OF I	NOTICE OF INTENTION TO TEST WATER SHUT-OFF	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE. NOTICE OF INTENTION TO DELLO OR ALTER CASING. NOTICE OF INTENTION TO ABANDON WELL  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). M. T.	P***	IZING
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.  NOTICE OF INTENTION TO PULL OR ALTER CASING.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA. MICE OF MEN MARK.  Pobruary 10 ,19 59  Chirmney Rock  Well No. 8-A is located 1863 ft. from Namph.  (It see, and see No.)  (County or Subdivision)  (County or Subdivision)  (State or Territory)  The elevation of the derrick floor above sea level is 5774 ft.  DETAILS OF WORK  (State names of and expected depths to objective sands; above sizes, weights, and location of proposed casings; indicate mudding jobs, coment-ling points, and all other important proposed work?)  2-6-59 Total Depth 1562'.  Ram 40 joints, 3-1/2", 15.50%, 3-55 Casing (1550') set at 1560' with 50 sacks regular cement, 50 sacks Pozmiz, 4% Gel., 1/40 Flocale per sack.  Held 10009/30 Minustee.  Top of cement by temperature survey at 670'.  REPLY DEPTH 1560:  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  El Paso Netural Gas Products Company  Address Fost Office Box 1565  Farmington, New Mexico  DETAILS OF WORK  (State of Territory)  (Meridian)  (Meridian)  (Meridian)  (Meridian)  (Meridian)  (State of Territory)  (St	NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	
NOTICE OF INTENTION TO PULL OR ALTER CASING NOTICE OF INTENTION TO ABANDON WELL  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DAYS). MEW MEY COUNTY, NOTICE OR OTHER DAYS). MEW MEXICO (KING). MEMORY OF SUBDIVISION). MEW MEXICO (FIGURE OF THE COUNTY). MEW MEXICO (FIGURE OF THE COUNTY). MEMORY OF SUBDIVISION). (State or The county). MEW MEXICO (FIGURE OF THE COUNTY). MEW MEXICO (FIGURE OF THE COUNTY). MEMORY OF SUBDIVISION). (State or The county). (State		PAIR
(Indicate above by Check Mark Nature of Report, Notice or Other Datas (Indicate States)  (Indicate above by Check Mark Nature of Report, Notice or Other Datas (Indicate States)  (Indicate above by Check Mark Nature of Report, Notice or Other Datas (Indicate States)  (Indicate above by Check Mark Nature of Report, Notice or Other Datas (Indicate States)  (Indicate above By Check Mark Nature of Report, Notice or Other Datas (Indicate States)  (Indicate Above By Check Mark Nature of Report, Notice or Other Datas (Indicate States)  (Indicate Above By Check Mark Nature of Report, Notice or Other Datas (Indicate States)  (Indicate Above By Check Mark Nature of Report, Notice or Other Datas (Indicate States)  (Indicate Above By Check Mark Nature of Report, Notice or Other Datas (Indicate States)  (Indicate Above By Check Mark Nature of Report, Notice Other Datas (Indicate States)  (Indicate Above By Check Mark Nature of Report, Notice Other Datas (Indicate States)  (Indicate Barbara Indicate States)  (Indicate Other Datas Indicate Indicat		· CD 1 0 4000
(State names of and expected depths to objective sands), show diese, weights, and langths of proposed easings; indicate mudding jobs, comentary and olicite, 19-1/2", 15-504, J-35 Casing (1350") set at 1360" with 30 secks regular coment by temperature survey at 670".  Lindowstand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  Eli Paso Natural Gas Products Company  Address Post Office Box 1565  Farmington, New Mexico  Petrology 10 , 19-59  Iline and 630 ft. from Eline of sec. 25  SENE/A Sec. 25	i ·	4-FR T-%-1898-
Chimney Sork  Well No. 8-A is located 1863 ft. from Siline and 630 ft. from E line of sec. 25  SE NE/4 Sec. 25  SIN 17W NIMPM  (Psp.) (Rango) (Maridian)  (Psp.) (County or Subdivision)  The elevation of the derrick floor above sea level is 5774 ft.  (State names of and expected depths to objective sands) show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work)  2-6-59 Total Depth 1542'.  Ran 40 joints, 3-1/2", 15.50\$, J-55 Casing (1350') set at 1360' with 50 secks regular coment, 50 sacks Fournix, 4% Gel., 1/4* Flocale per sack.  Held 1000\$/30 Minutes.  Top of coment by temperature survey at 670'.  El Paso Natural Gas Products Company  Address Farmington, New Mexico  ORIGINAL SIGNED BY: JUSEPH E. KREGE By—  Patrologum Raginager.	NOTICE OF INTENTION TO ABANDON WELL	i)) OCICE
Chimney Rock  Well No. 8-A is located 1863 ft. from Nilline and 630 ft. from E line of sec. 25  SE NE/4 Sec. 25 3LN 17W NMPM  (16 Sec. and Sec. No.) (Twp.) (Mange) (Meridian)  Horseshoe Gellup Ext. Sen Juan New Mexico  (Piak) (County or Subdivision) (State or Territory)  The elevation of the derrick floor above sea level is 5774 ft.  DETAILS OF WORK  (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed week?  2-6-59 Total Depth 1562.  Ran 40 joints, 5-1/2", 15.50%, J-55 Casing (1550") set at 1560" with 50 secks regular cement, 50 secks Pozmix, 4% Gel., 1/40 Flocale per seck.  Held 10009/30 Minutes.  Top of cement by temperature survey at 670".  El Paso Natural Gas Products Company  Address Formington, New Mexico  By  Petroleum Barinser	(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)	
Chimney Rock  Well No. 8-A is located 1863 ft. from   line and 630 ft. from   line of sec. 25  SE NE/4 Sec. 25 31N 17W NMPM  (Kango) (Meridian)  (Field) (County of Studivision) (State or Territory)  The elevation of the derrick floor above sea level is 5774 ft.  DETAILS OF WORK  (State names of and expected depths to objective analog show sizes, weights, and all other important proposed work)  2-6-59 Total Depth 1562'.  Ram 40 joints, 3-1/2", 15.50%, J-55 Casing (1350') set at 1360' with 50 secks regular cement, 50 secks Foamix, 4% Gel., 1/40 Flocale per seck.  Held 1000% 30 Minutes.  Top of cement by temperature survey at 670'.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  Company  El Paso Natural Gas Products Company  Address  Farmington, New Mexico  DRIGINAL SIGNED BY: JUSEPH E. KREGE		
SE NE/4 Sec. 25  31N 17W NMPM  (K Sec. and Sec. No.)  (Field)  (Field)  (Field)  (Field)  (Field)  (County or Subdivision)  (State or Territory)  The elevation of the derrick floor above sea level is 5774  ft.  DETAILS OF WORK  (State names of and expected depths to objective sands; show sixes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)  2-6-59 Total Depth 1562'.  Ram 40 joints, 5-1/2", 15.50%, J-55 Casing (1350') set at 1360' with 50 secks regular cement, 50 sacks Foxmix, 4% Gel., 1/4° Flocele par sack.  Held 1000°/30 Minustee.  Top of cement by temperature survey at 670'.  [I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  Company  Host Office Box 1565  Farmington, New Mexico  [State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-ing points, and lengths of proposed casings; indicate mudding jobs, cement-ing points, and lengths of proposed casings; indicate mudding jobs, cement-ing points, and lengths of proposed casings; indicate mudding jobs, cement-ing points, and lengths of proposed casings; indicate mudding jobs, cement-ing points, and lengths of proposed casings; indicate mudding jobs, cement-ing points, and lengths of proposed casings; indicate mudding jobs, cement-ing population, and lengths of proposed casings; indicate mudding jobs, cement-ing population, and lengths of proposed casings; indicate mudding jobs, cement-ing lengths of proposed work)	Chimney Rock	, 19.22
SE NE/4 Sec. 25  31N 17W NMPM  (K Sec. and Sec. No.)  (Field)  (Field)  (Field)  (Field)  (Field)  (County or Subdivision)  (State or Territory)  The elevation of the derrick floor above sea level is 5774  ft.  DETAILS OF WORK  (State names of and expected depths to objective sands; show sixes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)  2-6-59 Total Depth 1562'.  Ram 40 joints, 5-1/2", 15.50%, J-55 Casing (1350') set at 1360' with 50 secks regular cement, 50 sacks Foxmix, 4% Gel., 1/4° Flocele par sack.  Held 1000°/30 Minustee.  Top of cement by temperature survey at 670'.  [I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  Company  Host Office Box 1565  Farmington, New Mexico  [State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-ing points, and lengths of proposed casings; indicate mudding jobs, cement-ing points, and lengths of proposed casings; indicate mudding jobs, cement-ing points, and lengths of proposed casings; indicate mudding jobs, cement-ing points, and lengths of proposed casings; indicate mudding jobs, cement-ing points, and lengths of proposed casings; indicate mudding jobs, cement-ing points, and lengths of proposed casings; indicate mudding jobs, cement-ing population, and lengths of proposed casings; indicate mudding jobs, cement-ing population, and lengths of proposed casings; indicate mudding jobs, cement-ing lengths of proposed work)	Well No. 8-A is located 1863 ft. from N line and 630 ft. from E	ine of sec. 25
Horseshoe Gellup Ent.  (Pield)  (County or Subdivision)  (State or Territory)  The elevation of the derrick floor above sea level is 5774  ft.  DETAILS OF WORK  (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)  2-6-59 Total Depth 1562'.  Ran 40 joints, 3-1/2", 15.50%, J-55 Casing (1550') set at 1560' with 30 sacks regular cement, 50 sacks Fournix, 4% Gel., 1/4% Flocale per sack.  Held 1000%/30 Minustee.  Top of cement by temperature survey at 670'.  FEB 1 6 1959  OIL CON. COM.  COM.  Company  Address  Farmington, New Mexico  By  Fermington, New Mexico  Farmington, New Mexico	SE NB/4 Sec. 25 31N 17W NMPM	
(County or Subdivision)  (County or Subdivision)  (State or Territory)  (State or All longs of proposed casings; indicate mudding jobs, cement-  (State or Territory)  (State or	Carried Annual Control	lowles
DETAILS OF WORK  (State names of and expected depths to objective sands; show sizes, weights, and langths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)  2-6-59 Total Depth 1562'.  Ran 40 joints, 3-1/2", 15.500, J-55 Casing (1550') set at 1560' with 30 sacks regular cement, 30 sacks Fozmix, 4% Gel., 1/40 Flocele per sack.  Held 10000/30 Minutes.  Top of cement by temperature survey at 670'.  REFEVED  FEB 1 6 1959  OIL CON. COM.  OIL CON. COM.  OIL TO 3  Company  Address  Fost Office Box 1565  Farmington, New Mexico  By  Fattolesum Engineer		
Top of cement by temperature survey at 670°.  REFEND  FEB1 6 1959  OIL CON. COM.		th 10 marks
Company  Address  Fost Office Box 1565  Farmington, New Mexico  By  Petroleum Engineer	regular cement, 50 sacks Poumix, 4% Gel., 1/48 Flocale per sack.	
Address Farmington, New Mexico  By  Petroleum Bagineer	regular cement, 50 sacks Foumix, 4% Gel., 1/4* Flocale per sack. Held 1000*/30 Minutes.  Top of cement by temperature survey at 670*.  FEB 1 6	VED 5 1959 N. COM.
Farmington, New Mexico  By  By  Bringer	regular cement, 50 sacks Pozmix, 4% Gel., 1/4* Flocale per sack. Held 1000*/30 Minutes.  Top of cement by temperature survey at 670°.  FEB 1 6  OIL CON  I understand that this plan of work must receive approval in writing by the Geological Survey before operations.  El Paso Natural Gas Products Company	1959 N. COM.
ByBaringer	regular cement, 50 sacks Pozmix, 4% Gel., 1/4* Flocale per sack. Held 1000*/30 Minutes.  Top of cement by temperature survey at 670°.  FEB 1 6  OIL CON  Total Paso Natural Gas Products Company	S 1959 N. COM. T. 3 a may be commenced.
Petroleum Engineer	regular cement, 50 sacks Pozmix, 4% Gel., 1/40 Flocale per sack. Held 10000/30 Minutes.  Top of cement by temperature survey at 670°.  FEB 1 6  OIL CON  I understand that this plan of work must receive approval in writing by the Geological Survey before operations.  Company  Fost Office Box 1565  ORIGINAL SIGNED BY: Jacks and Jacks are sack.  ORIGINAL SIGNED BY: Jacks and Jacks are sack.  I dead to the foliage for the first and the foliage for the first and th	S 1959 N. COM. T. 3 a may be commenced.
Title Petroloum Engineer	regular cement, 50 sacks Pounix, 4% Gel., 1/4* Flocale per sack. Held 1000*/30 Minutes.  Top of cement by temperature survey at 670°.  FEB16  OIL CON  Company  El Paso Natural Gas Products Company  Address  Fost Office Box 1565  ORIGINAL SIGNED BY: Jacks Mexico	S 1959 N. COM. T. 3 a may be commenced.
	regular cement, 50 sacks Formix, 4% Gel., i/48 Flocale per sack. Held 10008/30 Minutes.  Top of cement by temperature survey at 670'.  RECELY  FEB 1 6  OIL CON  Total Company  El Paso Natural Gas Products Company  Address  Fost Office Box 1565  Farmingion, New Mexico  By  By	SEPH E. KREGE