

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Indian Agency Ute Indian	
Allottee Ute Mtn. Tribel	1
Lease No. Contract No. 14	-

20-604-85

CLINDDY MOTICES

	1 1		Y
NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PL NOTICE OF INTENTION TO TEST WATER		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO REDRILL OF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO SHOOT OR A		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.	1
NOTICE OF INTENTION TO PULL OR AL		SUBSEQUENT REPORT OF ABANDONMENT.	. 1
NOTICE OF INTENTION TO ABANDON W	1 1	SUPPLEMENTARY WELL HISTORY	
	Libbarrane	a A	
(INDICATE	ABOVE BY CHECK MARK NATUR	E OF REPORT, NOTICE, OR OTHER DATA)	
			vali i i i
	ted 700 ft. from S	Sarch 26 Sarch 26	, ,
//4 SE/14 20 (14 Sec. and Sec. No.)	31N 14d (Range (N N P M (Meridian)	
Verde Gallup	· · · · · · · · · · · · · · · · · · ·	•	
(Field)	San Juan (County or Subd	Nov Hexico (State or Territor)	
tate names of and expected depths to (objective sands; show sizes, weig ing points, and all other in	thts, and lengths of proposed casings; indicate mud aportant proposed work)	lding jobs, cemen
Well spudded on Jam Ran 2 jts. 13 3/8", landed at 72". Cem	uary 28, 1959 H-40, 48.0# surfaent with 65 sks. 1	this, and lengths of proposed casings; indicate mud apportant proposed work) ace casing on January 29, 195 regular cement with 2% calciums and the calciums are sured up to 500 psi on sur	9. Casin
Well spudded on Jam Ran 2 jts. 13 3/8", landed at 72". Ceme Drilled plug on Jam	uary 28, 1959 H-40, 48.0# surfaent with 65 sks. 1	ace casing on January 29, 195 regular cement with 2% calciv ressured up to 500 psi on sur	9. Casin
Well spudded on Jam Ran 2 jts. 13 3/8", landed at 72". Ceme Drilled plug on Jam ing - pressure held.	uary 28, 1959 H-40, 48.0# surfaent with 65 sks. 1 uary 30, 1959. Pr	ace casing on January 29, 195 regular cement with 2% calcium ressured up to 500 psi on sur	59. Casing am chloride rface cas-
Well spudded on Jam Ran 2 jts. 13 3/8", landed at 72". Ceme Drilled plug on Jam ing - pressure held.	uary 28, 1959 H-40, 48.0# surfaent with 65 sks. 1 uary 30, 1959. Pr	ace casing on January 29, 195 regular cement with 2% calcium ressured up to 500 psi on sur	9. Casin
Well spudded on Jam Ran 2 jts. 13 3/8", landed at 72". Ceme Drilled plug on Jam ing - pressure held.	uary 28, 1959 H-40, 48.0# surfaint with 65 sks. 1 uary 30, 1959. Pr	ace casing on January 29, 195 regular cement with 2% calcium ressured up to 500 psi on sur	59. Casing am chloride rface cas-
Well spudded on Jam Ran 2 jts. 13 3/8", landed at 72". Ceme Drilled plug on Jam ing - pressure held, I understand that this plan of work no	uary 28, 1959 H-40, 48.0# surfaint with 65 sks. 1 uary 30, 1959. Pr	ace casing on January 29, 195 regular cement with 2% calcium ressured up to 500 psi on sur	59. Casin m chlorid face cas-

U. S. GOVERNMENT PRINTING OFFICE 16-8437b-8