

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
SLM

99 JUN -1 PM 1:44

Sundry Notices and Reports on Wells

070 FARMINGTON, NM

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

990' FSL, 890' FWL, Sec. 22, T-31-N, R-11-W, NMPM

m

5. Lease Number
SF-078134

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number
Aztec A #1

9. API Well No.
30-045-10467

10. Field and Pool
Blanco Mesaverde

11. County and State
San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input checked="" type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

It is intended to plug the cliffhouse interval in the subject well according to the attached procedure.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 5/27/99
trc

(This space for Federal or State Office use)

APPROVED BY /S/ Duane W. Spencer Title Team Lead, Permitting Date JUN - 3 1999
CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCED

Aztec A #1
Mesaverde
990' FSL, 890' FWL
Unit M, Section 22, T-31-N, R-11-W
Latitude / Longitude: 36° 52.7921' / 107° 59.0323'
DPNO: 373001
Plug Cliffhouse Interval Procedure


CAUTION: This well produces H2S.

1. Hold safety meeting. Comply with all NMOCD, BLM and Burlington safety and environmental regulations. Test rig anchors and build blow pit prior to moving in rig. Notify **BROG Regulatory (Peggy Bradfield 326-9727)** and the appropriate Regulatory Agency prior to pumping any cement job. If an unplanned cement job is required, approval is required before the job can be pumped. If verbal approval is obtained, document approval in DIMS/WIMS. Allow as much time as possible prior to pump time in case the Agency decides to witness the cement job.
2. MOL and RU workover rig. Obtain and record all wellhead pressures. NU relief line. Blow well down and kill with 2% KCL water if necessary. ND WH and NU BOP with stripping head. Test and record operation of BOP rams. Have wellhead and valves serviced as necessary. Test secondary seal and replace/install as necessary.
3. Mesaverde, 2-3/8", 4.7# tubing is set at 4839'. Release donut, pick up additional joints of tubing and tag bottom. (Record depth.) PBTD should be at \pm 4860'. TOOH with tubing. Visually inspect tubing for corrosion and replace any bad joints. Check tubing for scale build up and notify Operations Engineer.
4. RU wireline, RIH with 7-5/8" RBP and set at \pm 4330'. RIH with dump bailer and dump \pm 10' of sand on top of RBP. RD wireline.
5. TIH with 7-5/8" fullbore packer on 2-3/8" tubing and set at + 4300'.
6. RU cement company. Pressure test tubing and RBP to 2500 psi. Release packer, TOOH to 3950' and re-set packer.
7. Squeeze into Cliffhouse perforations to 1000 psi with 180 sx of Class B cement (with .3% fluid loss). Displace cement with 14.5 Bbls of water (under displace by 1 Bbl.). Release pkr, reverse circulate hole. TOOH with 5 stands and reset pkr. Pressure squeeze with 500 psi and leave SI for 18 hrs. TOOH.
8. TIH with 6-3/4" bit, 3-1/8" drill collars (if necessary) and 2-3/8" tubing. Drill out cement. Pressure test squeeze to 500 psi for 15 minutes. If test is not successful, note leak off rate and contact Operations Engineer.
9. CO to RBP set at 4330'. TOOH. TIH with retrieving head and latch onto RBP. TOOH and lay down RBP.
10. TIH with 4-3/4" bit, bit sub and watermelon mill on 2-3/8" tubing and round trip to below perforations, cleaning out with air/mist. **NOTE: When using air/mist, minimum mist rate is 12 bph.** If scale is present, contact Operations Engineer to determine methodology for removing scale from casing and perforations.
11. TIH with one joint of 2-3/8" tubing with an expendable check on bottom and a seating nipple one joint off bottom then 1/2 of the 2-3/8" production tubing. Run a broach on sandline to insure that the tubing is clear. TIH with remaining 2-3/8" tubing and then broach this tubing. Replace any bad joints. CO to PBTD with air/mist. PU above the perforations and flow the well naturally, making short trips for clean up when necessary.
12. Land tubing at \pm 4820'. ND BOP and NU WH. Pump off expendable check. Connect to casing and circulate air to assure that expendable check has pumped off. Obtain pitot gauge up the tubing. If well will not flow up the tubing, make swab run to SN. RD and MOL. Return well to production.

Recommended:


Operations Engineer

Approved:

 5.24.99
Drilling Superintendent

Operations Engineer:

Mary Ellen Lutey
Office - (599-4052)
Home - (325-9387)
Pager - (324-2671)