

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
W.M. Galloway

3. ADDRESS OF OPERATOR
101-02 Petr. Plaza Bldg. Farmington, N.M.

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: **2150' FSL 2010' FEL**
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF
- FRACTURE TREAT
- SHOOT OR ACIDIZE
- REPAIR WELL
- PULL OR ALTER CASING
- MULTIPLE COMPLETE
- CHANGE ZONES
- ABANDON*
- (other)

SUBSEQUENT REPORT OF:

RECEIVED

AUG 19 1981

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

5. LEASE 14-20-551-45	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME UTE MOUNTAIN INDIAN	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME UTE INDIAN	
9. WELL NO. 3	
10. FIELD OR WILDCAT NAME VERDE GALLUP	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC. 10, T31N, R15W	
12. COUNTY OR PARISH SAN JUAN	13. STATE N.M.
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD) 5724	

NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/18/81 Fill hole with gel water. Circulate w/45" tubing sub spotted cement plug (17 sks.) over Gallup perf 1896' to 1864' and inside 5½" csq. rig down and moved .

6/1/81 Tagged cement 1781' inside 5½" csq., shot 5½" csq. 1223', pulled 5½" csq. , 6/2/81 Spotted 100' cement across stub (15 sks), spotted 100' cement plug (29 sks) across top of point lookout 450' to 550', spotted 50' cement plug (20 sks) across bottom of surface csq., spotted 10 sks cement top of hole, erect dry hole marker and clean location.

Subsurface Safety Valve: Manu. and Type _____

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *Kevin W. Bush* TITLE *Agent* DATE *8/14/81*

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

