1 - W. R. Johnston

1 - Phillips Pet. Co.

1 - File

Form C-122

Revised 12-1-55 MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS Pool Blanco Mesaverde Formation Mesaverde County San Juan Special Date of Test 8-3-56 Initial X Annual Company Pacific Horthwest Pipeline Corp. Lease 32-7 _____Well No. 15-34 Unit <u>N</u> Sec. <u>34</u> Twp. <u>32</u> Rge. <u>7</u> Purchaser <u>3,954.60</u> 5 1/2Wt. I.D. Set at 6,137.17 Perf. To Casing Tubing 2" Wt. I.D. _____Set at 6,114 Perf. _____To___ Gas Pay: From 5,742 To 6,138 L xG .605 -GL Bar.Press. 12 PSIA Producing Thru: Casing Tubing X Type Well Single
Single-Bradenhead-G. G. or G.O. Dual Date of Completion: 7-23-56 Packer Reservoir Temp. OBSERVED DATA Tested Through (Choke) (Meter) S.I. 11 days Type Taps Flow Data Tubing Data Casing Data (Choke) (Prover) Diff. Press. Temp. Press. Temp. Press. Temp. Duration No. (Line) of Flow $\circ_{\mathtt{F}}$. oF. $^{\circ}$ F. Size Size psig $h_{\mathbf{w}}$ psig psig Hr. 1,164 1,162 660 3/4 94 3 hrs. 303 94 FLOW CALCULATIONS Gravity Coefficient Pressure Flow Temp. Compress. Rate of Flow No. Factor Factor Factor Q-MCFPD Ft Fg (24-Hour) $h_{\mathbf{w}} p_{\mathbf{f}}$ $F_{\mathbf{p}\underline{\mathbf{v}}_{\underline{}}}$ @ 15.025 psia psia 14,1605 106 1,000 .9943 9958 1,486 PRESSURE CALCULATIONS Gas Liquid Hydrocarbon Ratio cf/bbl.
Gravity of Liquid Hydrocarbons deg. Specific Gravity Separator Gas Specific Gravity Flowing Fluid_P_c___1176 ____P²___1383.0 ___deg. (1-e^{-s}) $(\mathbf{F_cQ})^2$ P₊² $P_c^2 - P_w^2$ $(F_cQ)^2$ No. F_cQ $P_w 2$ Cal. $(1-e^{-s})$ $P_{\underline{\mathbf{w}}}$ Pt (psia) 99.2 1283.8 1.08 _MCFPD; n_ .75 = 1.0594 Absolute Potential: 1,574 COMPANY Pacific Borthwest Pipeline Corp. ADDRESS 405 West Broadway, Farmington, New Mexico AGENT and TITLE Clarence R. Wagner; Well Test Engineer WITNESSED COMPANY REMARKS

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w) . MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- P_{f} Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- F_t Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If P_{W} cannot be taken because of manner of completion or condition of well, then P_{W} must be calculated by adding the pressure drop due to friction within the flow string to P_{+} .

OIL CONSERVATION COMMISSION		
AZTEC DISTRICT OFFICE		
No. Copies Received 3		
DISTRIBUTION		
	NO. FURGISH E D	
Operator	·	
Santa Fe	/	
Proration (Mode		
State Land Office		
U S. G. S.	/	
Transporter		, de l'imme
i la	/	عسمه: