

Initial Deliverability  
Test

Form C-122-A  
Revised April 20, 1955

NEW MEXICO OIL CONSERVATION COMMISSION  
GAS WELL TEST DATA SHEET - - SAN JUAN BASIN

(TO BE USED FOR FRUITLAND, PICTURED CLIFFS, MESAVERDE, & ALL DAKOTA  
EXCEPT BARKER DOME STORAGE AREA)

Pool Elmwood Formation Mesa Verde County San Juan  
Purchasing Pipeline El Paso Natural Gas Company Date Test Filed \_\_\_\_\_  
Operator El Paso Natural Gas Lease San Juan 32-9 Well No. 2  
Unit J Sec. 30 Twp. 32 Rge. 9 Pay Zone: From 3275 To 3060  
Casing: OD 7 WT. 23 Set At 3203 Tubing: OD 2 WT. 4.7 T. Perf. 3228  
Produced Through: Casing \_\_\_\_\_ Tubing X Gas Gravity: Measured .69 Estimated \_\_\_\_\_  
Date of Flow Test: From 6/29/60 To 7/7/60 \* Date S.I.P. Measured 5/24/60  
Meter Run Size \_\_\_\_\_ Orifice Size \_\_\_\_\_ Type Chart \_\_\_\_\_ Type Taps \_\_\_\_\_

OBSERVED DATA

Flowing casing pressure (Dwt) \_\_\_\_\_ psig + 12 = \_\_\_\_\_ psia (a)  
Flowing tubing pressure (Dwt) \_\_\_\_\_ psig + 12 = \_\_\_\_\_ psia (b)  
Flowing meter pressure (Dwt) \_\_\_\_\_ psig + 12 = \_\_\_\_\_ psia (c)  
Flowing meter pressure (meter reading when Dwt. measurement taken):  
Normal chart reading \_\_\_\_\_ psig + 12 = \_\_\_\_\_ psia (d)  
Square root chart reading (\_\_\_\_\_) <sup>2</sup> x spring constant \_\_\_\_\_ = \_\_\_\_\_ psia (d)  
Meter error (c) - (d) or (d) - (c) \_\_\_\_\_ ± \_\_\_\_\_ = \_\_\_\_\_ psi (e)  
Friction loss, Flowing column to meter:  
(b) - (c) Flow through tubing; (a) - (c) Flow through casing \_\_\_\_\_ = \_\_\_\_\_ psi (f)  
Seven day average static meter pressure (from meter chart):  
Normal chart average reading \_\_\_\_\_ psig + 12 = \_\_\_\_\_ psia (g)  
Square root chart average reading (\_\_\_\_\_) <sup>2</sup> x sp. const. \_\_\_\_\_ = \_\_\_\_\_ psia (g)  
Corrected seven day avge. meter press. (p<sub>f</sub>) (g) + (e) \_\_\_\_\_ = \_\_\_\_\_ psia (h)  
P<sub>t</sub> = (h) + (f) \_\_\_\_\_ = \_\_\_\_\_ psia (i)  
Wellhead casing shut-in pressure (Dwt) 849 psig + 12 = 861 psia (j)  
Wellhead tubing shut-in pressure (Dwt) 734 psig + 12 = 746 psia (k)  
P<sub>c</sub> = (j) or (k) whichever well flowed through \_\_\_\_\_ = 746 psia (l)  
Flowing Temp. (Meter Run) 86 °F + 460 \_\_\_\_\_ = 546 °Abs (m)  
P<sub>d</sub> = 1/2 P<sub>c</sub> = 1/2 (l) \_\_\_\_\_ = 373 psia (n)

Q = \_\_\_\_\_ X  $\left( \frac{\text{FLOW RATE CALCULATION}}{\frac{\sqrt{(c)}}{\sqrt{(d)}}} \right) = \underline{115} \text{ MCF/da}$   
(Integrated)

DELIVERABILITY CALCULATION  
D = Q 115  $\left[ \frac{(P_c^2 - P_d^2)}{(P_c^2 - P_w^2)} \right]^n \frac{1.2650}{1.1927} = \underline{137} \text{ MCF/da.}$

SUMMARY  
P<sub>c</sub> = 746 psia  
Q = 115 Mcf/day  
P<sub>w</sub> = 476 psia  
P<sub>d</sub> = 373 psia  
D = 137 Mcf/day  
Company El Paso Natural Gas Company  
By H. L. Kendrick  
Title Sr. Gas Engineer  
Witnessed by \_\_\_\_\_  
Company \_\_\_\_\_

- \* This is date of completion test.
- \* Meter error correction factor

REMARKS OR FRICTION CALCULATIONS

GL	(1-e <sup>-S</sup> )	(F <sub>c</sub> Q) <sup>2</sup>	(F <sub>c</sub> Q) <sup>2</sup> (1-e <sup>-S</sup> ) R <sup>2</sup>	P <sub>t</sub> <sup>2</sup> (Column i)	P <sub>t</sub> <sup>2</sup> + R <sup>2</sup>	P <sub>w</sub>
			Friction Negligible			

D at 500 = 106

Perforated tubing - turned back on production 6/7/60.



