| Form (Feb. | 9-88<br>1961 | 11 <b>a</b><br>) |
|------------|--------------|------------------|
| Γ          | 1            |                  |

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

| Land Offic | co   | mto.I          | e     |      |
|------------|------|----------------|-------|------|
| Lease No.  | Q    | 79360          | ·     | -    |
| Unit       | S a  | Juan           | 32-€  | Uait |
|            | 14-1 | 06 <b>-</b> 00 | 1-446 |      |

| SUNDRY NOTICES A   | ND REPORTS ON WELLS   |
|--|---|
| WATER OF INVENTION TO DRIVE  | SUBSEQUENT REPORT OF WATER SHUT-OFF DE GELVE  |
| NOTICE OF INTENTION TO DRILL   | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.   |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF   | SUBSEQUENT REPORT OF ALTERING CASING  |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.  | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.   |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE  | SUBSEQUENT REPORT OF ABANDONMENT  |
| NOTICE OF INTENTION TO PULL OR ALTER CASING.   | SUBSEQUENT REPORT OF ABANDONMENT U. S. GEOLOGICAL SURVEY SUPPLEMENTARY WELL HISTORY.  |
| NOTICE OF INTENTION TO ABANDON WELL  | FARMINGTON, NEW MEXICO  |
| (NADICATE ABOVE BY CHECK MARK  | NATURE OF REPORT, NOTICE, OR OTHER DATA)  |
| (INDICATE ABOVE BT OF EACH MAIN.   |   |
|  | <u>October 30 , 19.53</u>   |
| Well No. 31-22 is located 1850 ft. from  | $\left\{\begin{array}{c} \mathbf{N} \\ \mathbf{S} \end{array}\right\}$ line and $\left\{\begin{array}{c} \mathbf{N} \\ \mathbf{W} \end{array}\right\}$ line of sec. |
| Sw/4 Sec. 22 328 (Y Sec. and Sec. No.) (Twp.)  |   |
| Elanco (Field) (County (   | or Subdivision) (State or Territory)  |
| The elevation of the derrick floor above sea le  | vel is GAR ft.  |
|  | ILS OF WORK   |
| (State names of and expected depths to objective sands; show six ing points, and all o   | tes, weights, and lengths of proposed casings; indicate mudding jobs, cement-<br>pther important proposed work)   |
| on 10-26-59 Total Depth 6398'.  Ran 59 Joints 5 1/2", J-55, 15.5# 1  193 sacks regular coment, 193 sacks tuff plug/sk, followed with 50 sack | iner (2404') set from 3966' to 6392' with Pozmix, 1/8# Flocele/sk. & 6% Gel, 1% fine a mest cement.   |
| Held 1000#/30 minutes.   | SEPFIVED  |
| Top of cement by temperature survey  | ot 3963'. /KLULI' 1059  |
|  | NOV 5 1930  |
|  | OIL CON. COM.   |
|  | DIST. 3   |
| I understand that this plan of work must receive approval in   | writing by the Geological Survey before operations, may be commenced.   |
| Company Il Paso Natural G.s Company  |   |
| Address Box 997  |   |
| Parmington, New Mexico   | ByBTIGINAL SIGNED H.E. McANALLY   |
|  | Title Fetroleum Engineer  |

