

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. 070459-B  
Unit Allison Unit

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED  
MAY 29 1958  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, NEW MEXICO

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	<input type="checkbox"/>
NOTICE OF INTENTION TO RE-DRILL OR REPAIR.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL.....		<input type="checkbox"/>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)


..... May 27 ....., 1958

Well No. 16(MD) is located 150 ft. from SW line and 1500 ft. from W line of sec. 15

SW 15 (1/4 Sec. and Sec. No.)      30N (Twp.)      7W (Range)      N.M.P.M. (Meridian)

H. Los Pinos & Blanco (Field)      San Juan (County or Subdivision)      New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 6866 ft.



DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On 5-25-58, Total Depth 3859'.  
 Run 109 joints 9 5/8", 40 & 36#, JS & JK (63 joints 40# on bottom, 46 joints 36# to surface) set at 3859'. Two stage cementing tool at 2908'. First stage 150 sacks regular cement, 150 sacks Fomix with 4# gal and 1/4# Floccule per sack followed with 100 sacks Neat cement, 1# Madkil/sk. in first and last 100 sacks. Second stage 550 sacks regular cement, 550 sacks Fomix with 4# gal and 1/4# Floccule per sack, 1# Madkil/sk. in first and last 100 sacks.  
 Top of cement by temperature survey on second stage at surface (cement circulated).

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 997

Farmington, New Mexico

By Original Signed D. C. Johnston

Title Petroleum Engineer

WASHINGTON  
MAY 10 1964  
U.S. DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT



OFFICE OF THE DIRECTOR

WASHINGTON, D.C. 20240