

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

14-20-600-3531

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NAVAJO UTE MTH, TRIB.

7. UNIT AGREEMENT NAME

MANY ROCKS GRILLUP BRO.

8. FARM OR LEASE NAME

MANY ROCKS

9. WELL NO.

1-W

10. FIELD AND POOL, OR WILDCAT

WATER BUTLY

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC. 17, T-31N, R-16W

12. COUNTY OR PARISH

SAN JUAN

13. STATE

N. M.

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

THE ATLANTIC REFINING COMPANY

3. ADDRESS OF OPERATOR

BOX 2197 FARMINGTON, N. M.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

SE NW (2253' FNL & 1865' FNL) SEC. 17

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

GR 5710' DF 5719'

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☒ STUD & CASING

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded at 5:00 P.M. 3/21/64. Drilled 17" hole to 110'. Ran 3 Jts. 13 3/8" O.D. 48" H-40 casing (94.37') set at 105.87'. Cemented w/ 125 sx cement plus 2% GEL. Cement circulated. Plug down at 1:30 P.M. 3/22/64. W.O.C. 36 hr. & tested casing w/ 500 psi o.k.

Drilled 12" hole to 3644' P.M. Ran 115 Jts. 8 5/8" O.D. 32 1/2" H-40 & J-55 casing w/ guide shoe & float collar (3608.11') set at 3617.86'. Cemented thru shoe w/ 575 sx class "c" cement plus 4% gel & 12% Gillisonite per sack and thru stage collar at 1858' w/ 270 sacks class "c" cement plus 4% gel and 12% Gillisonite per sack. First stage plug down at 12:25 PM 4/9/64. Second stage plug down 1:40 PM 4/9/64. W.O.C. 90 hrs. & drilled stage tool. Tested 8 5/8" cas. w/ 900# for 30 min. o.k.

18. I hereby certify that the foregoing is true and correct

SIGNED

B. J. Sartain

TITLE

ENGR. PAUL. J. V.

DATE

5/5/64


(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side



Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.