

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

FORM APPROVED
OMB NO. 1004-0137

Expires: February 28, 1995

5. LEASE DESIGNATION AND SERIAL NO.

SF-078472

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 32-7 Unit

8. FARM OR LEASE NAME, WELL NO.

SJ 32-7 Unit #34

9. API WELL NO.

30-045-21330

10. FIELD AND POOL, OR WILDCAT

Blanco Mesaverde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 27, T32N, R7W

12. COUNTY OR PARISH

San Juan

13. STATE

NM

1a. TYPE OF WELL:

OIL WELL ☐

GAS WELL ☒

DRY ☐

Other

b. TYPE OF COMPLETION:

NEW WELL ☐

WORK OVER ☐

DEEP-EN ☐

PLUG BACK ☐

DIFF. RESRV ☒

Other

2. NAME OF OPERATOR

Phillips Petroleum Company

3. ADDRESS AND TELEPHONE NO.

5525 Highway 64, NBU 3004, Farmington, NM 87401

505-599-3454

4. LOCATION OF WELL (Report location clearly and in accordance with any applicable requirements)

At surface

Unit A, 1080' FNL & 1190' FEL

At top prod. interval reported below

Same as above

At total depth

Same as above

14. PERMIT NO.

DATE ISSUED

15. DATE SPUDDED

10/6/73

16. DATE T.D. REACHED

10/16/73

17. DATE COMPL.(Ready to prod.)

11/28/99

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

6600'

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

8243'

21. PLUG, BACK T.D., MD & TVD

6172'

22. IF MULTIPLE COMPL., HOW MANY* 2 now

23. INTERVALS DRILLED BY

ROTARY TOOLS

X

CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION - TOP, BOTTOM, NAME (MD AND TVD)*

Blanco Mesaverde - 5586' - 5979'

25. WAS DIRECTIONAL SURVEY MADE

no

26. TYPE ELECTRIC AND OTHER LOGS RUN

GR/CCL/CBL

27. WAS WELL CORED

no

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9-5/8"	32.3#	234'	13-3/4"	225 cf	
7"	20#	3774'	8-3/4"	272 cf	
4-1/2"	11.6# & 10.5#	8243'	6-1/4"	690 cf	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					1-1/2"	5986'	no

30. TUBING RECORD

31. PERFORATION RECORD (Interval, size and number)

Blanco Mesaverde @ 1 spf .31" holes

See attached

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
5586' - 5979'	1500 gal 15% HCL & ballsealers
5586' - 5979'	147,000 # 20/40 Brown sand in
	139,300 gal 2 % KCL slickwater

33. PRODUCTION

DATE FIRST PRODUCTION SI		PRODUCTION METHOD (<i>Flowing, gas lift, pumping - size and type of pump</i>) flowing				WELL STATUS (<i>Producing or shut-in</i>) SI	
DATE OF TEST 11/26/99	HOURS TESTED 1 hr	CHOKE SIZE 1/2"	PROD'N. FOR TEST PERIOD →	OIL - BBL.	GAS - MCF. 1.552 mmcf	WATER - BBL. 48 bwpd	GAS - OIL RATIO
FLOW. TUBING PRESS.	CASING PRESSURE flowing-280 #	CALCULATED 24-HOUR RATE →	OIL - BBL.	GAS - MCF. 1.552 mmcf	WATER - BBL. 48 bwpd	OIL GRAVITY - API (CORR.)	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

SI-waiting to first deliver: Note-will flow MV only until pressure stabilizes

TEST WITNESSED BY

ACCEPTED FOR RECORD

35. LIST OF ATTACHMENTS

Will D/O CIBP & commingle DK/MV per R-11210. Application will be submitted & approved before commingled.

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE

Regulatory Assistant

*(See instructions and spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

38. GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Pictured Cliffs	no		These tops were from the DK completion reported dated 11/27/73.			
Mesaverde	5618'					
Pt Lookout	5850'					
Gallup	7094'					
Greenhorn	7914'					
Graneros	7968'					
Dakota	8096'					

San Juan 32-7 #34
SF-078472; Unit A, 1080' FNL & 1190' FEL
Section 27, T32N, R7W; San Juan County, NM

Mesaverde perforations @ 1 spf - .31" holes:

5979',	5954',	5937',	5921',	5913',	5892',	5887',	5880',	5879',	5877',	5873',	5872',	5866',
5864',	5863',	5860',	5857',	5855',	5854',	5851',	5798',	5795',	5761',	5760',	5756',	5745',
5744',	5735',	5717,	5714',	5710',	5707',	5672',	5645',	5642',	5627',	5719',	5586	38 holes