Form 3160-5 (November 1983) (Formerly 9-331)

JAN 08 1986

#### UNITED STATES SUBMIT IN TRIPLICATE\* (Other instructions on reverse side)

Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

SURVEY OR AREA

San Juan

Sec. 3, T31N, R10W

N.M.

BUREAU OF LAND MANAGEMENT	SF 078604	
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TEIBE NAME	
1.  OIL GAS WELL OTHER	7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR	8. FARM OR LEASE NAME	
El Paso Natural <u>Gas Company</u>	Scott	
3. ADDRESS OF OPIBATOR	9. WELL_NO.	
P.O. Box 4289, Farmington, New Mexico 87499-4289	13	
4. However, the takefore location clearly and in accordance with any State requirements.*  See also space 17 below.)	10. FIELD AND POOL, OR WILDCAT	
At surface	Blanco PC	
1640'N, 1100'W	11. SEC., T., B., M., OR BUK. AND SURVEY OR AREA	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

5905' GL

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

BUREAU OF LAND MANAGEMENTINTENTION TO:		SUBSEQUENT REPORT OF:			
FARMINGTON RESOURCE	ARE	A			
TEST WATER SHUT-OFF	!	PULL OR ALTER CASING		WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	i	MULTIPLE COMPLETE		FRACTUBE TREATMENT	ALTERING CASING
SHOOT OF ACIDIZE		ABANDON*	<u>X</u>	SHOOTING OR ACIDIZING	ABANDON MENT*
REPAIR WELL		CHANGE PLANS		(Other)	
(i)ther)			<u></u>	(Norg: Report results of m Completion or Recompletion	ultiple completion on Well Report and Log form.)

SOME PROPOSED OF COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

It is proposed to plug and abandon this non commercial well in the following manner:

Fill the 2 7/8" casing from surface to PBTD of 2893' with a 90 sx (106.2 cu.ft.) cement plug. Pressure displace a 60 sx (70.8 cu.ft.) cement plug down the surface casing annulus to fill from surface to 50' below the base of the surface casing at 182'.

Note: Ojo Alamo formation - top 1445', top of cement by temperature survey is 1450'.

Cut off wellhead and install dry hole marker.

JAN 131986

OIL CON. DIV. \ DIST. 3

SIGNED Loven W Fell	woller Sr. Production Engine	er APPROVED 1986
(This space for Federal or State office use)		AS AMILIADED
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	DATION 0 1086
Approved as to plugging of the well bere. Linbility under bend to received until		M. MILLENBACH
surface restoration to completed,	*See Instructions on Reverse Side	AREA MANAGER

## Instructions

eral and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Fed-

liem 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. State or Federal office for specific instructions.

In addition, such proposals and reports should include reasons for the abandonnanent; data on any former or present productive zones, or other zones with present significant fluid contents not prepared of the zones with present significant fluid contents not prepared of the zones with present significant fluid contents not prefet of the zones, or otherwise; depths, top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment. Hem 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices.

# PRIVACY ACT

The Privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that yeu be-furnished the following information in connection with information required by this application

AUTHORITY: 30 U.S.C. 181 et. seq., 451 et. seq., 25 U.S.C. et. seq.; 43 CFR 3160. PRINCIPAL PURPOSE: The information is to be used to evaluate, when appropriate, appropriate, approachions, and report completion of secondary well operations, on a Federal

ROUTINE USES. (1) Evaluate the equipment and procedures used during the proposed or completed subsequent well operations. (2) Request and grant approval to perform those actions covered by 43 CFR 3162.3—2(2). (3) Analyze future applications to drill or modify operations in light of data obtained and methods used. (4)(5) Information from the record and or the record will be transferred to appropriate Federal, State, local or feoreties, when relevant to civil, eriminal or regulatory investigations or prosecutions.

EFFECT OF NOT PROVIDING INFORMATION Filling of this notice and reportand disclosure of the information is mandatory once an oil or gas well is drilled.

The Paperwork Reduction Act of 1980 (44 U.S.C. 3501, et. seq.) requires us to informing that

This information is being collected in order to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

This information will be used to report subsequent operations once work is completed and when requested, to obtain approved to subsequent operations not previously authorized.

Response to this request is mandatory for the specific types of activities specified in 43 CFR Part 3160.

## BUREAU OF LAND MANAGEMENT Drawer 600 Farmington, New Mexico 87499-00600

Attachment to Notice of

Re: Permanent Abandonment

Intention to Abandon

Well: 13 300 75 -

#### CONDITIONS OF APPROVAL

- 1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal Leases."
- 2. The Farmington office (telephone (505) 325-4572) is to be notified in sufficient time for a representative to witness all plugging operations.
- 3. Blowout prevention equipment is required.
- 4. In addition to normal filling of pits and cleanup of location, additional surface restoration work <u>may</u> be required, i.e. ripping of pad and/or access road, reseeding, etc. We have asked the Surface Management Agency for the surface restoration requirements for this well and we should be able to furnish you these requirements within 30 days. After plugging the well and before making final clean-up, you should contact this office unless you have already been advised as to what additional surface restoration work is required.
- 5. The following modifications to your plugging program are to be made (when applicable):

Office Hours: 7:30 A.M. to 4:15 P.M.

### GENERAL REQUIREMENTS FOR PERMANENT ABANDONMENT OF WELLS ON FEDERAL LEASES FARMINGTON DISTRICT

- 1. Secure prior approval before changing the approved plugging program.
- Plugging equipment used shall have separate mixing and displacement pumps and a calibrated tank to assure proper displacement of plugs.
- 3. A proper tank or pit will be used to contain all fluids pumped from the well during plugging operations.
- 4. All cement plugs are to be placed through tubing (or drillpipe) and shall be a minimum of 25 sacks or 100 feet in length, whichever is greater.
- 5. Any cement plug placed when well is not full of fluid, or when well may be taking fluid, will be touched after cement has set to verify proper location.
- 6. Mud must be placed between plugs. Minimum consistency of plugging mud must be 9.2 lbs/gal. Brine is to be utilized for mixing mud where possible.
  - 7. Within 15 days after plugging work is completed, file Subsequent Report of Abandonment, form 9-331, in quintuplicate with District Supervisor, U.S.G.S., Drawer 600, Farmington, New Mexico 87499-00600. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. Show date well was plugged.
  - 8. All permanently abandoned wells are to be marked with a permanent monument, on which has been stenciled or beaded the well name, well number, and well location by quarter-quarter, section, township, and range. The monument is to be of steel pipe, not less than four inches in diameter, cemented permanently in the ground, and extending four feet above general ground level. The top should be closed with a screw cap, welding, or a cement plug.
- 9. After plugging work is completed:

a. Fill all pits, rat hole and cellar.

b. Clean well location of all equipment, concrete bases, pipe, junk and trash.

c. Cut or remove tie downs.

- d. If last well on lease, and no additional drilling is contemplated, fill tank battery pits, remove battery equipment, and clean and level battery location.
- e. Accomplish surface restoration as specified by the surface management agency or land owner.

All above are minimum requirements: The Subsequent Report of Abandonment will not be approved and the period of liability under the bond of record terminated until the lease is inspected and surface work approved.

Please advise this office when the well location is ready for final inspection.