

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

6. LEASE DESIGNATION AND SERIAL NO.

USA SFO78215-B

8. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Primo

9. WELL NO.

1A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesaverde

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 6, T31N, R10W

12. COUNTY OR PARISH

San Juan

13. STATE

N. M.

1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

Mesa Petroleum Co.

3. ADDRESS OF OPERATOR

P.O. Box 2009, Amarillo, Texas 79105

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1190' FN & WL, Sec. 6, T31N, R10W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, or etc.)

5943' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) 4-1/2" Liner

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

At 4632' Present Total Depth. On 9/23/75 ran 4-1/2" Liner as follows:

1.50 1 float shoe
39.88 1 jt 4-1/2" 10.5# CW55/insert float in top
1784.85 45 jts 4-1/2" 10.5# CW55
4.50 1 Burns Liner Hanger 7"x4-1/2"

1830.73' Total set at 4631' KBM. Top of Liner at 2801' KBM. Cemented as follows: pumped 30 bbls gelled water, 250 sacks 50-50 posmix, 1/4# floccelle per sack, 6/10 of 1% CFR-2, 5# gilsonite per sack, 2% gel, & 50 sacks 50-50 posmix, 2% Calcium Chloride, 6/10 of 1% CFR-2, 2% gel. Plugged down at 3:30 PM 9/23/75. Circulated 125 sacks.

SEP 30 1975

18. I hereby certify that the foregoing is true and correct

SIGNED

J. L. Farrell

TITLE

Operations Manager

DATE

9/26/75

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

XC: 5 USGS (2 copies to state)

1 Archer

DATE