UNITED STATES DEPARTMENT OF THE INTERIOR

UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE SF 078543		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME San Juan 32-7 Unit 8. FARM OR LEASE NAME		
1. oil gas W other	San Juan 32-7 Unit 9. WELL NO.		
2. NAME OF OPERATOR	#69 10. FIELD OR WILDCAT NAME		
Northwest Pipeline Corporation 3. ADDRESS OF OPERATOR	Basin Dakota		
P.O. Box 90, Farmington, N.M. 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 35, T32N, R7W		
AT SURFACE: 860' FNL & 1570' FEL AT TOP PROD. INTERVAL: Same as above AT TOTAL DEPTH: Same as above	12. COUNTY OR PARISH 13. STATE San Juan N.M. 14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	30-045-24777 15. ELEVATIONS (SHOW DF, KDB, AND WD) 6719' GR		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF THE TOTAL PROPERTION OF THE TOTAL PROPERTIES OF THE TOT	(NOTE Report results of multiple completion or zone change on Form 9-33).) MAY 2.2 19(10) OIL CON. COM. DIST. 3		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertiner	irectionally drilled, give substituted locations and		
5-1-81 Circ hole w/ 2% KCl & spotted 500 ga GR/CCl and perfed 18 holes from 8212' to HCl and dropped 25 balls, balled off, ran Western Pumped 20,000 gal pad followed w/ sanded off w/ 11,000# in perfs. MIR 24 B 4000#. Job completed at 1045 hrs 5-1-81. btm (8285'). PU Baker retrievamatic pkr	8278'. Pumped 1000 gal 7-1/2% junk basket and rec'ed 5 balls. 20/40 sand at 1 ppg. Well PM; AIR 23 BPM; MIP 4400#; AIP PU 3-7/8" bit & cleaned out to		
5-2-8] Established rate w/ 3000 gal 60# gel Pumped 1000 gal 15% HCl followed w/ 1000 at 1 ppg. MIR 6 BPM; AIR 5 BPM; MIP 6050 hrs 5-2-81. ISIP 3200#. Total sand in p	gal pad & 35,000# 20/40 sand #, AIP 6000#. Job done at 1530		
5-3-81 to 5-6-81 Blowing w/ compressor. Subsurface Safety Valve: Manu. and Type	Set @ Ft.		
18. I hereby certify that the foregoing is true and correct	F 10 01		
SIGNED Donna J. Brace (This space for Federal or State of	erk DATE 5-19-81		
APPROVED BYTITLE			
CONDITIONS OF APPROVAL, IF ANY:	and the second of the second o		

UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE SF 078543		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME San Juan 32-7 Unit		
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME San Juan 32-7 Unit		
1. oil gas X other	9. WELL NO. #69		
2. NAME OF OPERATOR Northwest Pipeline Corporation 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Bas in Dakota		
P.O. Box 90, Farmington, N.M. 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 35, T32N, R7W		
AT SURFACE: 860' FNL & 1570' FEL AT TOP PROD. INTERVAL: Same as above	12. COUNTY OR PARISH 13. STATE N.M.		
AT TOTAL DEPTH: Same as above 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO. 30-045-24777		
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6719' GR		
ABANDON* LJ (other)	(NOTE: Report results of multiple completion or zone change on Form 9–310.) IMAY 22 1980 OIL CON. COM. DIST. 3		
 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine 	ent to this work.)*		
5-7-81 Blowing well w/ compressor. Ran 26 EUE 8RD USS seamless tbg set at 8168' w/	l jts (8160') of 2-3/8", 4.7#, J-55 1.780 SN on top of btm jt.		
5-8-81 to 5-10-81 Blowing well w/ compresso	or		
5-11-81 Rig released at 0600 hrs. Cleaning	g up after frac.		
NOW WAITING ON IP TEST.			

Subsurface Safety Valve: Manu. and Type			Set @ Ft.
18. I hereby certify that the foregoing is trusted in the signed in thes	TITLE Production Clerk	DATE	5-19-81.
	(This space for Federal or State office use)		
APPROVED BY	TITLE	DATE	3 190 -

*See Instructions on Reverse Side