

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Southland Royalty Company
3. ADDRESS OF OPERATOR
P.O. Drawer 570, Farmington, New Mexico 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 930' FNL & 1720' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA


REQUEST FOR APPROVAL TO:
TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Casing Report

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE
SF-078115
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Grenier
9. WELL NO.
#23-E
10. FIELD OR WILDCAT NAME
Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 31, T31N, R11W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6013' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-05-81 Ran 9 joints (390') of 4-1/2", 11.60#, K-55 and 160 joints (6779') of 4-1/2", 10.50#, K-55 casing set at 7181'. DV tools set at 2731' and 5119'. Cemented 1st stage with 180 sacks of Class "B" 50/50 Poz with 6% gel and 1/4# gel flake per sack. Followed by 50 sacks of Class "B" Neat & 2% CaCl₂. Plug down at 6:00 A.M. 5-5-81. Cemented 2nd stage with 200 sacks of Class "B" 50/50 Poz with 6% gel and 1/4# gel flake per sack. Followed by 50 sacks of Class "B" Neat and 2% CaCl₂. Plug down at 10:30 A.M. 5-5-81. Cemented 3rd stage with 400 sacks of Class "B" 50/50 Poz with 6% gel and 1/4# gel flake per sack. Followed by 50 sacks of Class "B" Neat and 2% CaCl₂. Plug down at 2:30 P.M. 5-5-81. Top of cement at 1250'.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Cathy Greyson TITLE Drilling Clerk DATE May 6, 1981

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

MAY 12 1981

*See Instructions on Reverse Side

FARMINGTON DISTRICT
RY 6413