

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR

SUPRON ENERGY CORPORATION

3. ADDRESS OF OPERATOR

P.O. Box 808, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 900 ft./S ; 1735 ft./E line

AT TOP PROD. INTERVAL: Same as above

AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE

SF 078244

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Taliaferro

9. WELL NO.

3-E

10. FIELD OR WILDCAT NAME

Blanco Mesaverde; Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 31, T-31N, R-12W, NMPM

12. COUNTY OR PARISH

San Juan

13. STATE


New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

5938 R.K.B.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spudded 12 1/4" surface hole at 1:00 p.m. 7-27-81.
2. Drilled 12 1/4" surface hole to total depth of 260 ft. R.K.B.
3. Ran 6 joints of 8-5/8", 24.00#, H-40 casing and set at 260 ft. R.K.B.
4. Cemented with 200 sacks of class "B" with 3% calcium chloride. Plug down at 6:00 p.m. 7-27-81. Cement circulated to surface.
5. Waited on cement for 12 hours.
6. Pressure-tested casing to 800 P.S.I. for 30 minutes. Held OK.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Kenneth E. Roddy

TITLE Production Supt. DATE July 30, 1981

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: