

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR  
BASIN MINERALS, INC.
3. ADDRESS OF OPERATOR C/O Walsh Engr. & Prod. Corp.  
P.O. Drawer 419, Farmington, N.M. 87499
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 830'FNL, 1090'FWL  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <input type="checkbox"/>	<input type="checkbox"/>

5. SE  
SF-078097
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Federal
9. WELL NO.  
100
10. FIELD OR WILDCAT NAME  
Blanco Mesa Verde
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 27-T31N-R11W  
N.M.P.M.
12. COUNTY OR PARISH  
San Juan
13. STATE  
N.M.
14. API NO.  
30-045-25851
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5835'GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

12/19/83 T.D. 5196'. Ran 59 joints 4-1/2", 10/50 lbs., KS casing set at 5151' with liner hanger at 2664'. Cemented with 396 cu. ft. 50-50 Pozmix (2% Gel) with 6-1/4 lbs. Gilsonite per sack. Cement circulated. Float Collar 5109

**RECEIVED**  
FEB 29 1984  
OIL CON. DIV.  
DIST. 3

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

FOR: BASIN MINERALS, INC.  
18. I hereby certify that the foregoing is true and correct

SIGNED **EWELL N. WALSH** Walsh Engr. & Prod.  
Ewell N. Walsh, P.E. President Corp. DATE 12/21/83

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DEC 22 1983

\*See Instructions on Reverse Side

**OPERATOR**

Examination reference area

BY *Smr*