40. OF COPIES SCCEIVES	1	7		
DISTRIBUTION		7		
SANTA FE		1		
FILE		1		
U.S.G.S.		1		
LAND OFFICE		1		
OPERATOR		1		

## OIL CONSERVATION DIVISION P. O. BOX 2088

U.S.G.S.		NEW MEXICO 8/1501	Revised 10-1-
		. /	5a. Indicate Type of Lease
OPERATOR			State X Fee
	·	• .	5. State Oil & Gas Lease No. E-3150-1
SUN NOT USE THIS FORM FOR	NDRY NOTICES AND REPORT A PROPOSALS TO DRILL OF TO DEEPEN OF LICATION FOR PERMIT - " (FORM C-101)	SON WELLS PLUG BACK TO A DIFFERENT RESERVOIR. FOR SUCH PROPOSALS.	
OIL CAS WELL Name of Operator	OTHER+		7. Unit Agreement Name
El Paso Natural Gas Company			8. Farm of Lease Name Brookhaven Com
Address of Operator P. O. Box 4289, Farmington, NM 87499		9. Well No.	
Location of Well			17 10. Field and Pool, or Wildow
UNIT LETTER N	840 FEET FROM THE SOL	ith LINE AND 1690	Aztec Pictured Cliffs
THE West LINE, SE	CTION 36 TOWNSHIP	·	
		heiher DF, RT, GR, etc.) 5895† GL •	12. County San Juan
Chec NOTICE OF	k Appropriate Box To Indication To:	ate Nature of Notice, Report or C	ther Data
		SUBSEQUE	NT REPORT OF:
RFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
MPORARILY ABANDON	<b>6</b> 11411.65	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
	CHANGE PLANS	CASING TEST AND CEMENT JOB	C 1 1 12 12
OTHER			Spud Well X
Describe Proposed or Completed	Operations (Clearly state all pertiner	it details, and give pertinent dates, includin	
9-19-85	3 jts. 8 5/8", 24 Cemented with 110 gel flake/sk (130	0:00 p. m. 9-18-85. Di .0#, K-55 surface casin sks. Class "B", 3% ca cu.ft.). Circulated t	ng set at 138'. alcium chloride, 1/4# to surface. WOC 12
9-19-85	3 jts. 8 5/8", 24 Cemented with 110 gel flake/sk (130	.0#, K-55 surface casin	ng set at 138'. alcium chloride, 1/4# to surface. WOC 12
9-19-85	3 jts. 8 5/8", 24 Cemented with 110 gel flake/sk (130	.0#, K-55 surface casing sks. Class "B", 3% castured to cu.ft.). Circulated to	ng set at 138'. alcium chloride, 1/4# to surface. WOC 12
	3 jts. 8 5/8", 24 Cemented with 110 gel flake/sk (130 hours, Tested 60	.0#, K-55 surface casing sks. Class "B", 3% caston cu.ft.). Circulated to 0#/30 minutes, held ok	ng set at 138'. alcium chloride, 1/4# to surface. WOC 12
	3 jts. 8 5/8", 24 Cemented with 110 gel flake/sk (130	.0#, K-55 surface casing sks. Class "B", 3% caston cu.ft.). Circulated to 0#/30 minutes, held ok	ng set at 138'. alcium chloride, 1/4# to surface. WOC 12
	Cemented with 110 gel flake/sk (130 hours, Tested 60 hours, Tested 60	.0#, K-55 surface casing sks. Class "B", 3% caston cu.ft.). Circulated to 0#/30 minutes, held ok	ng set at 138'. alcium chloride, 1/4# to surface. WOC 12