

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

El Paso Exploration Company

3. ADDRESS OF OPERATOR

PO Box 4289, Farmington, NM 87499

4. LOCATION OF WELL (Report location clearly and in accordance with BUREAU OF LAND MANAGEMENT FARMINGTON RESOURCE AREA
See also space 17 below.)
At surface

1660'S, 1750'W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6767'GL

5. LEASE DESIGNATION AND SERIAL NO.

NM 58887

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Newco

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 20, T-32-N, R-9-W
NMPM

12. COUNTY OR PARISH 13. STATE

San Juan

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-19-85

TD 3973'. Ran 95 jts. 7", 20.0#, K-55 intermediate casing, 3961' set @ 3973'. Cemented with 280 sks. Class "B" 65/35 Poz, with 6% gel, 2% calcium chloride and 1/2 cu.ft./sack perlite (540 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (118 cu.ft.). WOC 12 hours. Held 1200#/30 min. Top of cement at 2400' by T.S.

Perforated 2 squeeze holes at 1825'. Squeeze cemented Ojo Alamo formation with 150 sks. Class "B" with 2% calcium chloride (177 cu.ft.). Good circulation throughout job.

8-24-85

TD 6450'. Ran 62 jts. 4 1/2", 10.5#, J-55 casing liner, 2533' set @ 6350'. Float collar set @ 6340'. Top of liner hanger @ 3817'. Cemented with 50 sks. Class "B" 50/50 Poz, 2% gel and 0.6% fluid loss additive (62 cu.ft.) and 280 sks. Class "B" 50/50 Poz with 2% gel, 6.25# gilsonite, 1/4# flocele, and 0.6% fluid loss additive (381 cu.ft.) WOC 18 hours. Circulated out gel water.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Drilling Clerk

8-27-85

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

SEP 03 1985

DATE

1985

OIL CON. DIV.

*See Instructions on Reverse Side DIST. 3

NMOCC

FARMINGTON RESOURCE AREA

BY