## UNITED STATES

## DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports	s on Wells		
	<u></u>	5.	Lease Number SF-080517
1. Type of Well GAS		6.	If Indian, All. or Tribe Name
	AN 18	7.	Unit Agreement Name
2. Name of Operator	into jamena	+ 2.7 ×	
BURLINGTON RESOURCES OIL & GAS COMPANY			
	- 1754. 356 전 	8.	
3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 3	26-9700	9.	Payne #11 API Well No. 30-045-26804
4. Location of Well, Footage, Sec., T, R, M		10.	Field and Pool
590'FNL 810'FEL, Sec.27, T-32-N, R-10-W, NM	PM	11.	Basin DK/Cedar Hill FT County and State San Juan Co, NM
12. CHECK APPROPRIATE BOX TO INDICATE NATURE O	F NOTICE, REPO	RT, OTHER	DATA
	pe of Action		
_X_ Notice of Intent Abandonme		nge of Pl	
Subsequent Report Plugging		Construc	tion Fracturing
Casing Re		er Shut o	
Final Abandonment Altering X Other -	Casing Cor	nversion t	o Injection
13. Describe Proposed or Completed Operation	s		
It is intended to install a pump in the procedure and wellbore diagram.	subject well a	according	to the attached PECEIVER 1 2: 35
	rue and correc	et.	

## **Payne #11** PUMPING UNIT INSTALLATION PROCEDURE 2/8/99

## Unit A, Section 27, T32N, R10W, San Juan County, New Mexico Aircare Lat. 36 57.70' Aircare Long, 107 51.77'

- 1. MIRU PULLING UNIT.
- 2. BLOW DOWN TBG. KILL WELL W/ WATER ONLY IF NECESSARY
- 3. NDWH / NUBOP.
- 4. PU AT LEAST 2 JTS. OF TBG. TIH TO TAG FOR FILL.
- 5. TOH STANDING BACK 2-3/8" TBG. (TBG. IS SET @ 3652', THERE ARE 116 JTS. OF 2-3/8" 4.7# J-55 WITH F NIPPLE @ 3619').
- 6. PU 4-3/4" BIT ON 2-3/8" TBG. AND TIH TO COTB, CIRC. HOLE CLEAN. TOH W/ SAME.
- 7. TIH W/ 2-3/8" TBG. STRING AND LAND TBG. @ 3696". PURGE VALVE WILL BE ON BOTTOM W/ 2-3/8"x10" PUP JOINT(3686'-3696'), 2-3/8"x6" PUP JOINT(3680'-3686'), 2-3/8"x4" PERFORATED SUB(3676'-3680') AND 2-3/8" SN @ 3676'.
- 8. HANG TBG. IN DONUT. NDBOP / NUWH.
- 9. TIH W/ NEW TOP HOLD DOWN ROD PUMP (2"x1-1/4"x10'x14' RHAC-Z). 4' SECTION CUP TYPE PLUNGER. RUN THREE - 1-1/4" SINKER BARS. 144 - 3/4" GRADE D SUCKER RODS (W/ SPRAY METAL COUPLINGS), A SET OF 3/4" PONY RODS (21.41.61.81) TO SPACE OUT, ONE - 1-1/4"x 22 - 3/4" PIN POLISHED ROD AND ONE - 1/1/4"x1-1/2"x10" POLISHED ROD LINER.
- 10. SEAT THE DOWNHOLE PUMP, HANG HORSES HEAD ON, SPACE PUMP
- 11. LOAD TBG. . PRESSURE TEST.
- 12. START PUMPING UNIT. AND TEST OK (ADJUST SPACING IF NEEDED).
- 13. RDMO.

COMPLY WITH ALL FEDERAL, STATE AND LOCAL RULES AND REGULATIONS RELATING TO OIL AND GAS OPERATIONS.

Prepared: E.J. Giles Office: 326-9584

Home: 325-8164 Pager: 324-2636

Approved: Drilling Supt.

Payne #11
(Current)
Cedar Hill Fruitland Coal
Unit A, Section 27, T32N, R10W, San Juan County, New Mexico

