

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1130' FSL, 860' FWL, Sec. 9, T-32-N, R-10-W, NMPM

5. Lease Number

NM-013367

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number
Brown #100

9. API Well No.
30-045-26957

10. Field and Pool
Basin Fruitland Coal

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment

Type of Action

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other - Pump Installation

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

It is intended to install a pump in the subject well according to the attached procedure and wellbore diagram.

14. I hereby certify that the foregoing is true and correct.

Signed

Deanna Cole

Title Regulatory Administrator Date 1/5/00

trc

(This space for Federal or State Office use)

APPROVED BY

Chip Harrison

Title

Acting Team Lead

Date

1/5/00

CONDITION OF APPROVAL, if any:

NMOCB

Brown #100
PUMPING UNIT INSTALLATION PROCEDURE
12/30/99

Unit M, Section 9, T32N, R10W, San Juan County, New Mexico

Aircare Lat. 36 59.70'
Aircare Long. 107 53.57'

1. MIRU PULLING UNIT.
2. BLOW DOWN TBG. KILL WELL W/ WATER ONLY IF NECESSARY.
3. NDWH / NUBOP.
4. PU AT LEAST 2 JTS. OF TBG. - TIH TO TAG FOR FILL.
5. TOH STANDING BACK 2-3/8" TBG. (TBG. IS SET @ 3458', THERE ARE 107 JTS. OF 2-3/8" 4.7# J-55 WITH F NIPPLE @ 3426').
6. PU 4-3/4" BIT ON 2-3/8" TBG. AND TIH TO COTB, CIRC. HOLE CLEAN. TOH W/ SAME.
7. TIH W/ 2-3/8" TBG. STRING AND LAND TBG. @ 3492'. PURGE VALVE WILL BE ON BOTTOM W/ 2-3/8"x10' PUP JOINT(3482'-3492'), 2-3/8"x6' PUP JOINT(3476'-3482'), 2-3/8"x4' PERFORATED SUB(3472'-3476') AND 2-3/8" SN @ 3472'.
8. HANG TBG. IN DONUT. NDBOP / NUWH.
9. TIH W/ NEW TOP HOLD DOWN ROD PUMP (2"x1-1/4"x10'x14' RHAC-Z), 4' SECTION CUP TYPE PLUNGER. RUN THREE - 1-1/4" SINKER BARS, 136 - 3/4" GRADE D SUCKER RODS (W/ SPRAY METAL COUPLINGS), A SET OF 3/4" PONY RODS (2', 4', 6', 8') TO SPACE OUT, ONE - 1-1/4"x 22 - 3/4" PIN POLISHED ROD AND ONE - 1/1/4"x1-1/2"x10' POLISHED ROD LINER.
10. SEAT THE DOWNHOLE PUMP, HANG HORSES HEAD ON, SPACE PUMP.
11. LOAD TBG. , PRESSURE TEST.
12. START PUMPING UNIT, AND TEST OK (ADJUST SPACING IF NEEDED).
13. RDMO.

COMPLY WITH ALL FEDERAL, STATE AND LOCAL RULES AND REGULATIONS RELATING TO OIL AND GAS OPERATIONS.

E.J. Giles 12-30-99

Prepared: E.J. Giles
Office: 326-9584
Home: 325-8164
Pager: 324-2636

Bruce W. Brown 1-4-00

Approved: Drilling Supt.

Pump Company is Energy Pump & Supply
(505)564-2874

Brown #100
(Current)
Cedar Hill Fruitland Basal Coal
Unit M, Section 9, T32N, R10W, San Juan County, New Mexico

Completed: 1/14/89
 Recavitated: Mar-97

