UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Sundry Not	ices and Reports or	. Wells			
1. Type of Well GAS			5.	Lease Number SF-078459-B If Indian, A Tribe Name	
2. Name of Operator		NAR 1 5 199	g 🛂.	Unit Agreeme Allison Unit	
BURLINGTON	, we				
RESOURCES	& GAS COMPANY (0)	il Cons. I	8. פשטעש	Well Name &	Number
3. Address & Phone No. of Opera	tor			Allison Unit	
PO Box 4289, Farmington, NM	87499 (505) 326-9	700	9.	API Well No.	
4. Location of Well, Footage, S	ec. T. R. M		10	30-045-27139 Field and Po	
1080'FSL 790'FWL, Sec.14, T-			10.	Basin Fruitl	
			11.	County and S San Juan Co,	
12. CHECK APPROPRIATE BOX TO IN			, OTHER	DATA	
Type of Submission		of Action	6 51.		
X Notice of Intent	Abandonment Recompletion		e of Pla onstruct		
Subsequent Report	Recompletion Plugging Back			Fracturing	
<u> </u>	Casing Repair				
Final Abandonment	Altering Casi _X_ Other -	ng Conve	rsion to	Injection	
13. Describe Proposed or Comp It is intended to install	_	ect well acc	ording t	o the	
	e and wellbore diag		oruzng (
					2.7 2.0 1.00 2.00
14. I hereby certify that the Signed Signed State State Signed	foregoing is true (DWM) Title Regul		strator		
				TLW	
(This space for Federal or Stat APPROVED BY (MP) (APPROVAL, if any:		Franceal	Date _	3///99	
Title 18 U.S.C. Section 1001, makes it a crime for United States any false, fictitious or fraudulent s					

Allison #127 PUMPING UNIT INSTALLATION PROCEDURE

<u>Unit M, Section 14, T32N-R7W, San Juan County, New Mexico</u> <u>Lat. 36.975840 / 36° 58.55'</u> <u>Long. 107.542850 / 107° 32.57'</u>

- 1. MIRU pulling unit.
- 2. RU and POOH with 7/8" rod string. There are 137 rods and a PCP rotor.
- 3. NDWH/NUBOP.
- 4. PU two joints of tubing. TIH to tag for fill.
- 5. TOH standing back 2-3/8" tubing. (Tubing is set @3461' there are 111 jts of 2-3/8" 4.7# J-55 with a PCP stator assembly on bottom).
- 6. PU 4-3/4" bit on tubing and TIH to COTD. Circ hole clean. (Note: PBTD is @ 3509').
- 7. TIH w/2-3/8" tubing string and land tubing @ 3500'. Purge valve will be on bottom followed by pup joint, perforated sub, and seating nipple. Space out as needed with pup joints.
- 8. Hang tubing in donut. NDBOP / NUWH.
- 9. TIH w/ new 1.25" top hold down pump, existing 7/8" Grade D sucker rods, polished rod, and polished rod liner (Note: Vendor contact is listed below).
- 10. Seat the downhole pump, hang horses head, and space out pump.
- 11. Load tubing, and pressure test.
- 12. Start pumping unit and test (adjust spacing if needed).
- 13. RDMO.

COMPLY WITH ALL FEDERAL, STATE AND LOCAL RULES AND REGULATIONS RELATING TO OIL AND GAS OPERATIONS.

Prepared: D.W. Mussett

Pump Vendor: Energy Pump

Leo Noyes 564-2874

Allison Unit #127

Basin Fruitland Coal Unit M, Section 14, T32N, R7W, San Juan County, New Mexico

