

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

F.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-045-27248
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. E-5386, B-11370, E-3150
7. Lease Name or Unit Agreement Name Pubco State Com
8. Well No. 1A
9. Pool name or Wildcat Blanco Mesa Verde
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6061' GR

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)	
1. Type of Well: OIL WELL ☐ GAS WELL ☒ OTHER ☐	2. Name of Operator GREAT WESTERN DRILLING CO.
3. Address of Operator 2550 La Plata Hwy, Farmington, NM 87401	4. Well Location Unit Letter <u>I</u> : <u>935</u> Feet From The <u>East</u> Line and <u>1690</u> Feet From The <u>South</u> Line Section <u>36</u> Township <u>31N</u> Range <u>11W</u> NMPM <u>San Juan</u> County
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: Spud well & run long string ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8-1-89

Spud 14-3/4" hole @ 7:15 P.M. 8-1-89.

8-1-89

Ran 8 jts. 40.5# J-55 10-3/4" csg. total of 247', set @ 259 K.B., cemented w/235 sx class "B" 2% Ca. cl. cement circulated good. W.O.C. 12 hrs. Nipple up test B.O.P & csg. 800# 30 min. o.k.

8-6-89

Ran 74 jts. 20 & 30# J-55 8rd 7" csg. 2885 set @ 2897' K.B. cemented w/150 sx class "B" + 43# of Howco glass bubbles + 1% halad 22-A + 1/4# flocele + 2% ca. cl. mixed @ 8.6# per gal. followed w/100 sx class "B" + 1% ca. cl. mixed @ 15.6# 1 gal. cement circulated to surface.

8-9-89 W.O.C. 14 hr. nipple up B.O.P., test B.O.P. & 7" csg. to 1000# 30 min. o.k.

Ran 61 jts. 10.5# J-55 ST&C 4 1/2" csg. w/Baker liner hanger, hanger @ 2793' bottom @ 5258' 2' off bottom, cemented w/325 sx class "B" + 1% ca. cl. plug down @ 2:00 A.M. 8-9-89, reverse out cement above liner, released rig 4:00 A.M.

8-9-89 (logs run oper hole) GR. SP, comp, neutron density, caliper & DI guard

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE D. E. Bayler TITLE Superintendent DATE 10-27-89

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT # 3 DATE OCT 30 1989

CONDITIONS OF APPROVAL, IF ANY: