

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

REGULATORY AFFAIRS  DATE  NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5.  (This space for Federal or State office use)  ACCEPTED FOR RECORD  APPROVED BY  TITLE  DATE  DATE	SUNDRY NOTICES AND REP	PORTS ON WELLS
MERIDIAN OIL INC.  3. ADDRESS & PHONE NO. OF OPERATOR P O BOX 4289 FARMINGTON, NM 87499  4. LOCATION OF WELL 2040'FSL 790'FWL  4. LOCATION OF WELL 2040'FSL 790'FWL  10. FIELD, POOL, OR WILDCAT BASIN FRUITLAND COAL 11. SEC. T. R. M OR BLK. SEC. 33 T32N ROGW NMPM  14. PERMIT NO. 15. ELEVATIONS 6438'GL 12. COUNTY RIO ARRIBA NM  16. SUBSEQUENT REPORT OF: SPUD  17. Describe proposed or completed operations  SPUD DATE: 100990 SPUD TIME: 1330  TD 232' Ran 5 jts of 9 5/8" 36.0 K K-55 casing, 212' set @ 224' Cemented with 160 sacks of Class B cement with 1/4# Flocele/sack and 3% calcium chloride, (189 cu ft.). Circulated 17 bbl to surface. WOC 12 hours. Pressure tested to 600 psi for 30 minutes. Held OK.  DATE: 101290  TD 3005', Ran 70 jts of 7" 20.0 K K-55 casing, 2993' set @ 3005' Lead with 572 sacks of Class B cement 65/35 Poz, 6% gel, 2% CaCl2, 5 cu ft perlite (1150 cu ft.). Tail with 100 sacks of Class B cement with 2% CaCl2 118 cu ft.). Circulated 50 bbl to surface.  18. AUTHORIZED BY: REGULATORY AFFAIRS  NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5.  TITLE  APPROVED BY  TITLE  TMOTE 2.3 1990		SF-078772
P O BOX 4289 FARMINGTON, NM 87499  4. LOCATION OF WELL 2040'FSL 790'FWL  10. FIELD, POOL, OR WILDCAT BASIN FRUITLAND COAL 11. SEC. T. R. M OR BLK. SEC. 33 T32N RO66W NMPM  14. PERMIT NO. 30.045-27420  15. ELEVATIONS 6438'GL  12. COUNTY REPORT OF: SPUD  17. Describe proposed or completed operations  SPUD DATE: 100990  SPUD TIME: 1330  TD 232' Ran 5 jts of 9 5/8" 36.0# K-55 casing, 212' set @ 224' Cemented with 160 sacks of Class B cement with 1/4# Flocele/sack and 3% calcium chloride, (189 cu ft.). Circulated 17 bbl to surface. WOC 12 hours. Pressure tested to 600 psi for 30 minutes. Held OK.  DATE: 101290  TD 3005', Ran 70 jts of 7" 20.0# K-55 casing, 2993' set @ 3005' Lead with 572 sacks of Class B cement 65/35 POZ, 6% gel, 2% CaCl2, .5 cu ft perlite ( 1150 cu ft.). Tail with 100 sacks of Class B cement with 2% CaCl2 (-118 cu ft.). Circulated 50 bbl to surface.  NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5.  (This space for Federal or State office use)  ACCEPTED FOR RECORD		
2040'FSL 790'FWL  BASIN FRUITLAND COAL  11. SEC. T. R. M OR BLK. SEC. 33 T32N R06W NMPM  14. PERMIT NO.  30.045-27420 6438'GL  12. COUNTY RIO ARRIBA  13. STATE RIO ARRIBA  14. SEC. 33 T32N R06W NMPM  15. ELEVATIONS 6438'GL  16. SUBSEQUENT REPORT OF: SPUD  17. Describe proposed or completed operations  SPUD DATE: 100990 SPUD TIME: 1330  TD 232' Ran 5 jts of 9 5/8" 36.0# K-55 casing, 212' set @ 224' Cemented with 160 sacks of Class B cement with 1/4# Flocele/sack and 3% calcium chloride, ( 189 cu ft.). Circulated 17 bbl to surface. WOC 12 hours. Pressure tested to 600 psi for 30 minutes. Held OK.  DATE: 101290  TD 3005', Ran 70 jts of 7" 20.0# K-55 casing, 2993' set @ 3005' Lead with 572 sacks of Class B cement 65/35 POZ, 68 gel, 2% CaCl2, 5 cu ft perlite ( 1150 cu ft.). Tail with 100 sacks of Class B cement with 2% CaCl2 (-118) cu ft.). Circulated 50 bbl to surface.  18. AUTHORIZED BY  REGULATORY AFFAIRS  NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5.  (This space for Federal or State office use)  ACCEPTED FOR RECORD	P O BOX 4289	ROSA UNIT 9. WELL NO.
30-045-27420 6438'GL RIO ARRIBA NM  16. SUBSEQUENT REPORT OF: SPUD  17. Describe proposed or completed operations  SPUD DATE: 100990 SPUD TIME: 1330  TD 232' Ran 5 jts of 9 5/8" 36.0# K-55 casing, 212' set @ 224' Cemented with 160 sacks of Class B cement with 1/4# Flocele/sack and 3% calcium chloride, (189 cu ft.). Circulated 17 bbl to surface. WOC 12 hours. Pressure tested to 600 psi for 30 minutes. Held OK.  DATE: 101290  TD 3005', Ran 70 jts of 7" 20.0# K-55 casing, 2993' set @ 3005' Lead with 572 sacks of Class B cement 65/35 Poz, 6% gel, 2% CaCl2, .5 cu ft perlite (1150 cu ft.). Tail with 100 sacks of Class B cement with 2% CaCl2 (118 cu ft.). Circulated 50 bbl to surface.  18. AUTHORIZED BY:  REGULATORY AFFAIRS  NM  APPROVED BY  TITLE  ACCEPTED FOR RECORD	2040'FSL 790'FWL	BASIN FRUITLAND COAL 11. SEC. T. R. M OR BLK.
SPUD DATE: 100990 SPUD TIME: 1330  TD 232' Ran 5 jts of 9 5/8" 36.0# K-55 casing, 212' set @ 224' Cemented with 160 sacks of Class B cement with 1/4# Flocele/sack and 3% calcium chloride, (189 cu ft.). Circulated 17 bbl to surface. WOC 12 hours. Pressure tested to 600 psi for 30 minutes. Held OK.  DATE: 101290  TD 3005', Ran 70 jts of 7" 20.0# K-55 casing, 2993' set @ 3005' Lead with 572 sacks of Class B cement 65/35 Poz, 6% gel, 2% CaCl2, .5 cu ft perlite (1150 cu ft.). Tail with 100 sacks of Class B cement with 2% CaCl2 (118 cu ft.). Circulated 50 bbl to surface.  18. AUTHORIZED BY:  REGULATORY AFFAIRS  NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5.  (This space for Federal or State office use)  ACCEPTED FOR RECORD  APPROVED BY  TITLE  MOTE 2.3 1990	30-045-27420 6438'GL	
SPUD DATE: 100990 SPUD TIME: 1330  TD 232' Ran 5 jts of 9 5/8" 36.0# K-55 casing, 212' set @ 224' Cemented with 160 sacks of Class B cement with 1/4# Flocele/sack and 3% calcium chloride, (189 cu ft.). Circulated 17 bbl to surface. WOC 12 hours. Pressure tested to 600 psi for 30 minutes. Held OK.  DATE: 101290  TD 3005', Ran 70 jts of 7" 20.0# K-55 casing, 2993' set @ 3005' Lead with 572 sacks of Class B cement 65/35 Poz, 6% gel, 2% CaCl2, .5 cu ft perlite (1150 cu ft.). Tail with 100 sacks of Class B cement with 2% CaCl2 till cu ft.). Circulated 50 bbl to surface.  18. AUTHORIZED BY:  MOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5.  (This space for Federal or State office use)  APPROVED BY  TITLE  MOTE: 23 1990		
TD 3005', Ran 70 jts of 7" 20.0# K-55 casing, 2993' set @ 3005' Lead with 572 sacks of Class B cement 65/35 Poz, 6% gel, 2% CaCl2, .5 cu ft perlite ( 1150 cu ft.). Tail with 100 sacks of Class B cement with 2% CaCl2 ( 118 cu ft.). Circulated 50 bbl to surface.  18. AUTHORIZED BY: REGULATORY AFFAIRS  NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5.  (This space for Federal or State office use)  ACCEPTED FOR RECORD  APPROVED BY  TITLE  DATE	SPUD DATE: 100990 SPUD TIME: 1330  TD 232' Ran 5 jts of 9 5/8" 36.00  Cemented with 160 sacks of Class Flocele/sack and 3% calcium chlocaled control of the	0 0# K-55 casing, 212' set @ 224' s B cement with 1/4# oride,( 189 cu ft.). WOC 12 hours.
REGULATORY AFFAIRS DATE  NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5.  (This space for Federal or State office use)  APPROVED BY  TITLE  DATE  DATE  DATE  DATE	TD 3005', Ran 70 jts of 7" 20.0; Lead with 572 sacks of Class B of Poz, 6% gel, 2% CaCl2, .5 cu ft Tail with 100 sacks of Class B of	cement 65/35 perlite ( 1150 cu ft.). cement with
(This space for Federal or State office use)  ACCEPTED FOR RECORD  APPROVED BY  TITLE  MART: 23 1990		
APPROVED BY TITLE MACHE 23 1990	=======================================	
CONDITION OF APPROVAL, IF ANY:  FARMINGTON RESOURCE AREA	*************	1000 E 2 3 1990

Marie Car