

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE*
(Other 16% Users on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. NAME OF OPERATOR
BASF Corporation

3. ADDRESS OF OPERATOR
P.O. Box 23 Towaoc, CO 81334

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
Surface: 1550' FSL & 810' FEL

14. PERMIT NO.
30-045-27422

15. ELEVATIONS (Show whether OF, RT, GR, etc.)
5556' ungraded ground

5. LEASE DESIGNATION AND SERIAL NO.
751-88-0001

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
UTE MT. UTE

7. UNIT AGREEMENT NAME
NA

8. FARM OR LEASE NAME
UTE MT. UTE

9. WELL NO.
28-43

10. FIELD AND POOL, OR WILDCAT
Basin Dakota

11. SEC. T. R. M. OR R.R. AND SURVEY OR AREA
28-31N-14W NMPM

12. COUNTY OR PARISH
San Juan

13. STATE
NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

well status

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

SPUDDED Well at 2100 hrs, 09/24/89. Drilled 12-1/4" hole to 275'.

Ran 6 joints 8-5/8" 24# J-55 ST&C casing to 274'. Cemented back to surface with 207 ft³ class "B" cement. Circulated 65 ft³ to surface. Tested to 2100 PSIG for 30 min. on 9-26-89. HELD OK

Drilled 7-7/8" hole to a total depth of 5297'. Ran 5-1/2" 15.5# J-55 LT&C casing to 5297'. Cemented first stage with 375 ft³ 50-50 Pozmix & 177 ft³ of class "B". Cemented second stage with 2996 ft³ Halliburton Lite followed by 59 ft³ class "B" cement. Circ 840 ft³ to surface. TESTED (SG. TO 3000 PSIG FOR 30 MIN ON 11-1-89. HELD OK

RELEASE RIG on 10/12/89.

RECEIVED

JAN 31 1990

OIL CON. DIV.
DIST. 3

3/23/90

ACCEPTED FOR RECORD

JAN 25 1990

By: San Juan Resource Area
Bureau of Land Management

RECEIVED

MAR 27 1990

OIL CON. DIV

18. I hereby certify that the foregoing is true and correct

SIGNED Don H. Hensley

TITLE Drig & Prod Supervisor

DATE 01/24/90

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

DURANGO OFFICE COPY

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.