

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.

3004527497

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

AMOCO PRODUCTION COMPANY

Attention

Nancy I. Whitaker

8. Well No.

1

P.O. Box 800

Denver

Colorado

80201

303-830-5039

9. Pool name or Wildcat

BASIN FRUITLAND COAL

4. Well Location

Unit Letter

A

: 1000

Feet From The

NORTH

Line and

900

Feet From The

EAST

Line

Section

28

Township

31N

Range

9W

NMPM

SAN JUAN

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

6143 GR

11.

Check Appropriate Box to Indicate Nature of Notice Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☒ REPAIR

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRUSU 2/5/97

SET PLUG IN F NIPPLE TO PULL TBG. C/O 2834 - 2972 W/AIR AND 10 BPH SOAP MIST.

DEEPEN WELL 2972' TO 2996' WITH 6 1/4" DRILL BIT AND CIRCULATED WITH FOAM. C/O BRIDGES 2783 - 2996' W/1500 CFM AIR AND 10 BPH SOAP MIST. SURGE NATURAL 3 TIMES, 190 PSI IN 1.5 HRS BUILDUP, SURGE 9 TIMES AT 350# WITH 1500 CFM AIR.

UNDERREAM 2760-2996 WITH 6.25" X 9.5" BIT. SURGE DOWN CASING 5 TIMES WITH 1500 CFM AIR AT 300# PSI. TIH & C/O BRIDGES 2885-2890, 2980-2986, W/1500 CFM AIR & FOAM. C/O W/1500 CFM AIR AND 10 BPH SOAP MIST. CIRCULATE WELL CLEAN.

RAN GR/CORR LOG 2500-2987. RAN 4 1/2" FLUSH HOINT LINER, PERFORATED 2809-2819, 2827-2849, 2879 - 2891, 2943 - 2977 W/ 4 JSPF, .370 DIA AND 120 DEGREE PHASING AND 14 GMS CHARGE. CIRCULATED W/30 BBLs PRODUCED WATER. TIH TO RETREIVE PLUG, LANDED 2 3/8" TBG AT 2990', RAN 3/4" RODS AND PUMP LANDED AT 2993'. PRESSURE TESTED RODS & PUMP TO 500 PSI. HELD OKAY....
RDSUMO 2/13/97

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Nancy I. Whitaker

TITLE

Staff Assistant

DATE

03-26-1997

TYPE OR PRINT NAME

Nancy I. Whitaker

TELEPHONE NO.

303-830-5039

(This space for State

APPROVED BY

Johnny Robinson

TITLE

DEPUTY OIL & GAS INSPECTOR, DIST. #3

DATE

MAR 28 1997

CONDITIONS OF APPROVAL, IF ANY: