

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. SF-078543
2. NAME OF OPERATOR PHILLIPS PETROLEUM COMPANY		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 300 W. Arrington, Suite 200, Farmington, NM 87401		7. UNIT AGREEMENT NAME San Juan 32-7 Unit
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit N, 1230' FSL & 1570' FWL		8. FARM OR LEASE NAME
14. PERMIT NO. 30-045-27745		9. WELL NO. 207
15. ELEVATIONS (Show whether OF, RT, OR, etc.) 6651'		10. FIELD AND POOL, OR WILDCAT Basin Fruitland Coal
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 27, T22N, R7W
		12. COUNTY OR PARISH San Juan
		13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANE ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(Other) Drilling Operations

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-18-90 - MIRU Aztec Well Service Rig No. 289. Spudded 12 1/4" hole at 12:30 P.M. Ran 9 5/8", 36#, K-55, ST&C casing set at 287.06. RU Dowell and cement with 250 SX C1 'G' cement with 2% CaCl₂ and 1/4# flocele/sk. Circ. 83 SX cement. Plug down at 10:15 P.M. Bumped plug with 860 psi. Float held. WOC 10 hrs. NU BOP and test to 600 psi - Okay.

RECEIVED
SEP 18 1990
OIL CON. DIV.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

R. A. Allred

TITLE Drilling Supervisor

DATE 8-27-90

(This space for Federal or State office use)

(505) 599-3403

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

SEP 04 1990

*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA

BY