

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

91 JUL 24 AM 11:16

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other Coal Seam

2. Name of Operator

Amoco Production Company Attn: John Hampton

3. Address and Telephone No.

P.O. Box 800, Denver, Colorado 80201

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1520' FSL, 1805' FWL, Sec. 26, T32N-R11W

5. Lease Designation and Serial No.

SF-078039

6. If Indian, Allottee or Tribe Name

N.M.

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Barnes Gas Com F #1

9. API Well No.

30 045 27810

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal Gas

11. County or Parish, State

San Juan, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Perf & Frac
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Perf: 5/24/91

2928'-2933', W/8 JSPF, .5" diam., 40 shots open.
2937'-2939', W/8 JSPF, .5" diam., 16 shots open.
2946'-2949', W/8 JSPF, .5" diam., 24 shots open.
2959'-2962', W/8 JSPF, .5" diam., 24 shots open.
2997'-2999', W/8 JSPF, .5" diam., 16 shots open.
3061'-3064', W/8 JSPF, .5" diam., 24 shots open.
3072'-3074', W/8 JSPF, .5" diam., 16 shots open.
3077'-3085', W/8 JSPF, .5" diam., 64 shots open.
3109'-3112', W/8 JSPF, .5" diam., 24 shots open.
3168'-3183', W/8 JSPF, .5" diam., 120 shots open.

Frac: 6/1/91

Frac down casing with 1320 BW and 570 BBls CO2 pad,
started sand and pumped 1020 BW and 502 BBls CO2 during sand
stage, 21030# 40/70 brady sn, 139470 20/40# arizona sn.
AIR 88 BPM, AIP 1800psi.

14. I hereby certify that the foregoing is true and correct

Signed John Hampton

Title Sr. Staff Admin. Supv.

Date 7/16/91

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any: _____

Title _____

ACCEPTED FOR RECORD

AUG 19 1991

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

Perf: 5/24/91

2928'-2933', W/8 JSPF, .5" diam., 40 shots open.
2937'-2939', W/8 JSPF, .5" diam., 16 shots open.
2946'-2949', W/8 JSPF, .5" diam., 24 shots open.
2959'-2962', W/8 JSPF, .5" diam., 24 shots open.
2997'-2999', W/8 JSPF, .5" diam., 16 shots open.
3061'-3064', W/8 JSPF, .5" diam., 24 shots open.
3072'-3074', W/8 JSPF, .5" diam., 16 shots open.
3077'-3085', W/8 JSPF, .5" diam., 64 shots open.
3109'-3112', W/8 JSPF, .5" diam., 24 shots open.
3168'-3183', W/8 JSPF, .5" diam., 120 shots open.

Frac: 6/1/91

Frac down casing with 1320 BW and 570 BBls CO2 pad,
started sand and pumped 1020 BW and 502 BBls CO2 during sand
stage, 21030# 40/70 brady sn, 139470 20/40# arizona sn.
AIR 88 BPM, AIP 1800psi.

Perf: 5/24/91

2928'-2933', W/8 JSPF, .5" diam., 40 shots open.
2937'-2939', W/8 JSPF, .5" diam., 16 shots open.
2946'-2949', W/8 JSPF, .5" diam., 24 shots open.
2959'-2962', W/8 JSPF, .5" diam., 24 shots open.
2997'-2999', W/8 JSPF, .5" diam., 16 shots open.
3061'-3064', W/8 JSPF, .5" diam., 24 shots open.
3072'-3074', W/8 JSPF, .5" diam., 16 shots open.
3077'-3085', W/8 JSPF, .5" diam., 64 shots open.
3109'-3112', W/8 JSPF, .5" diam., 24 shots open.
3168'-3183', W/8 JSPF, .5" diam., 120 shots open.

Frac: 6/1/91

Frac down casing with 1320 BW and 570 BBls CO2 pad,
started sand and pumped 1020 BW and 502 BBls CO2 during sand
stage, 21030# 40/70 brady sn, 139470 20/40# arizona sn.
AIR 88 BPM, AIP 1800psi.