UNITED STATES

Submitted Coat Co	rm 3160-5 UNI (1990)	TED STATES NT OF THE INTERIOR	Budget Burean No. 1004-0135 Expires: March 31, 1993
Do not use this form are proposals to drill or to deepen or reentry to a different reservoir. Compared Co	· · · · · · · · · · · · · · · · · · ·	/	
Submit in South agreement Designation of the Geopean or recently to a different reservoir. Submit in Tripulation for Permit Tripulation for Such proposals	SUNDRY NOTICES	AND REPORTS ON WELLS	
Submitted Coat Co	Do not use this torm for proposals to di	fill Of to deepen or reentry to a different reservoir.	6. If Indian, Allottee or 1 ripe Name
Same Congression Same			7. If Unit or CA, Agreement Designation
Address and Telephone No. 2550 La Plata Hwy, Farmington, NM 87401 Location of Weil (Fossage, Sec. T. R. M. or Survey Description) 1740' FSL, 890' FWL, NW/SW, Sec. 11, T-31N, R-11W CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF SUBMISSION No. Recompletion No. Recompletion Subsequent Report Final Abandonment Notice Describe Proposed of Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally of the Change of Plate (Note: Report to this work.)* CHANGE ORIGINAL APD. FOR PRODUCTION CASING: FROM: 54" CASING TO 44" 10.5# J-55 8 rd. TO BE CEMENTED WITH 827 CU. FT. LEAD CEMENT OF 65/35 POSMIX CONSISTING OF 65/36 CEL., 2% CA. CL. + 4# SX. OF PERLITE, FOLLOWED WITH 100 SX. REG. NEAT 1. Ibereby coppy, that the foreigness inve and correct APPROVED APPROVED	 00 0		8. Well Name and No.
Address and Telephone No. 2550 La Plata Hwy, Farmington, NM 87401 10. Field and Fool, or Exploratory Area Basin Fruitland Coal 1740' FSL, 890' FWL, NW/SW, Sec. 11, T-31N, R-11W CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF SUBMISSION Nonce of finent Abandonment Abandonment Nonce Plass New Construction New Constru	2. Name of Operator		Mudge Gas Com "A" #1
Address and Telephone No. 2550 La Plata Huy, Farmington, NM 87401 10. Field and Pool, or Euploratory Area Basin Fruitland Coal 11. County or Parish, State San Juan, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Plugging Back Casing Repair Casing Repair Altering Casing Dispose Water (Note, Reportantial adjusted operations (Clearly state all pertinent details), and give pertinent dates, including estimated date of starting any proposed work. If well is directionally of the CEMENTED WITH 827 CU. FT. LEAD CEMENT OF 65/35 POSMIX CONSISTING OF CALL 72 CA. CL. 44 S. O. PERLITE, FOLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 2% CA. CL. TOTAL CEMENT 945 CU. FT. 7-5/8" HOLE WILL BE CIRCULATED TO SURFACE. 1 hereby ceptyh, that the foregoings is true and correct APPROVED APPROVED	GREAT WESTERN DRILLING	COMPANY	
Location of Well (Footage, Sec., T., R. M., or Survey Description) Basin Fruitland Coal	Address and Telephone No.		30-045-28107
Basin Fruitland Coal 1740' FSL, 890' FWL, NW/SW, Sec. 11, T-31N, R-11W San Juan, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Recompletion Plugging Back Casing Repair Conversaon to Injection Dispose Water (Note: Reportment date, including estimated date of starting any proposed work. If well is directionally of give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* CHANGE ORIGINAL APD. FOR PRODUCTION CASING: FROM: 5½" CASING TO 4½" 10.5% J-55 8rd. TO BE CEMENTED WITH 827 CU. FT. LEAD CHEMENT OF 65/35 POSMIX CONSISTING OF 6% GELL, 2% CA. CL. + 4% SX. OF PERLITE, FOLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 2% CA. CL. TOTAL CEMENT 945 CU. FT. 7-5/8" HOLE WILL BE LOGGED AND CALIFERED, CEMENT USED TO BE 50% OVER CALIFER AND WILL BE CIRCULATED TO SURFACE.	2550 La Plata Hwy, Fa	rmington, NM 87401	
1740' FSL, 890' FWL, NW/SW, Sec. 11, T-31N, R-11W San Juan, NM CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Recompletion Now Construction Now Recompletion Conversion to Injection Conversion to Injection Construction are Recompleted Special and Interventical depths for all markers and zones pertinent dates, including estimated date of starting any proposed work. If well is directionally of give substrace locations and measured and true vertical depths for all markers and zones pertinent to this work.)* CHANGE ORIGINAL APD. FOR PRODUCTION CASING: FROM: 5½" CASING TO 4½" 10.5# J-55 8rd. TO 86 CEMENTED WITH 827 CU. FT. LEAD GEMENT OF 65/35 POSMIX CONSISTING OF 67 GELL, 2% CA. CL. + 4# SX. OF PERLITE, FOLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 2% CA. CL. TOTAL CEMENT 945 CU. FT. 7-5/8" Holle WILL BE LOGGED AND CALIFERED, CEMENT USED TO BE 50% OVER CALIPER AND WILL BE CIRCULATED TO SURFACE. APPROVED	Location of Well (Footage, Sec., T., R., M., or Survey D	escription)	Basin Fruitland Coal
San Juan, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION Notice of Intent Abandonment Recompletion Abandonment Non-Routine Fricturing Non-Routine Fricturing Abandonment Non-Routine Fricturing Altering Casing Conversion to Injection Dispose Water (Non-Routine Fricturing other Non-Routine Fricturing Conversion to Injection Dispose Water (Non-Routine Fricturing other Non-Routine Fricturing Conversion to Injection Dispose Water (Non-Routine Fricturing Conversion to Injection Non-Routine Fricturing Conversion to Injection Dispose Water (Non-Report results of multiple completion or Report results of multiple completion or Report results of multiple completion or Report results of multiple completion or Recompletion or Recompletion Report and Fricturing and Proposed work. If well is directionally or give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* CHANGE ORIGINAL APD. FOR PRODUCTION CASING: FROM: 5½" CASING TO 4½" 10.5# J-55 8 rd. To be CEMENTED WITH 827 CU. FT. LEAD JUMENT OF 65/35 POSMIX CONSISTING OF 67. CDL, 2% CA. CL. + 4# SX. OF PERLITE, FOLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 2% CA. CL. TOTAL CEMENT 945 CU. FT. 7-5/8" HOLE WILL BE LOGGED AND CALIPERED, CEMENT USED TO BE 50% OVER CALIPER AND WILL BE CIRCULATED TO SURFACE.	1740' FSI 890' FUI NU/SU See 11 m 21 P 22 P 22 P		
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION Notice of Intent	1/40 1019 000, 1429	NW/SW, Sec. II, T-SIN, K-IIW	
TYPE OF SUBMISSION Notice of Intent			
Abandonment Recompletion New Construction New Recompletion & Posts & Water Shut-Off Note: Recompletion & Posts & Water Shut-Off Note: Recompletion & Recompletion & Recompletion & Recompletion & Recompletion & Recompletion & Posts & Water Shut-Off Note: Recompletion & Recompletion & Recompletion & Recompletion & Recompletion & Posts & Water Shut-Off Note: Recompletion & Non-Recompletion & Non-Recompleti	CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
Subsequent Report Subsequent Report Plugging Back Non-Routine Fracturing Saling Repair Water Shut-Off Conversion to Injection Dispose Water Investigate locations and measured and true vertical depths for all markers and zones pertinent dates, including estimated date of starting any proposed work. If well is directionally of give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* CHANGE ORIGINAL APD. FOR PRODUCTION CASING: FROM: 5½" CASING TO 4½" 10.5# J-55 8 rd. TO bef CEMENTED WITH 827 CU. FT. LEAD GEMENT OF 65/35 POSMIX CONSISTING OF 62 CEL, 2% CA. CL. + 4# SX. OF PERLITE, FOLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 2% CA. CL. TOTAL CEMENT 945 CU. FT. 7-5/8" HOLE WILL BE LOGGED AND CALIPPERD, CEMENT USED TO BE 50% OVER CALIPER AND WILL BE CIRCULATED TO SURFACE. APPROVED	TYPE OF SUBMISSION	TYPE OF ACTION	
Subsequent Report Subsequent Report Plugging Back Non-Routine Fracturing Water Shut-Off Casting Repair Water Shut-Off Other Construction Dispose Water (Note: Report results of multiple completion or Recompleted Operations (Clearly state all pertinent details, and gave pertinent dates, including estimated date of starting any proposed work. If well is directionally of give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* CHANGE ORIGINAL APD. FOR PRODUCTION CASING: FROM: 5½" CASING TO 4½" 10.5# J-55 8rd. TO be CEMENTED WITH 827 CU. FT. LEAD CEMENT OF 65/35 POSMIX CONSISTING OF 67. CEL., 2% CA. CL. + 4# SX. OF PERLITE, FOLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 2% CA. CL. TOTAL CEMENT 945 CU. FT. T-5/8" HOLE WILL BE LOGGED AND CALIPERED, CEMENT USED TO BE 50% OVER CALIPER AND WILL BE CIRCULATED TO SURFACE.	Notice of Intent	Abandonment	Y Change of Plans
Subsequent Report Final Abandonment Notice Plugging Back Water Shut-Off Water Shut-Off Conversion to Injection Dispose Water Conversion to Injection Dispose Water Conversion to Injection Dispose Water Conversion to Injection Co	<u> </u>		
Casing Repair Casing Repair Water Shut-Off Conversion to Injection Dispose Water Dispose Water Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally of give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* CHANGE ORIGINAL APD. FOR PRODUCTION CASING: FROM: 5½" CASING TO 4½" 10.5# J-55 8rd. To be CEMENTED WITH 827 CU. FT. LEAD CEMENT OF 65/35 POSMIX CONSISTING OF 6% CEL, 2% CA. CL. + 4# SX. OF PERLITE, FOLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 2% CA. CL. TOTAL CEMENT 945 CU. FT. 7-5/8" HOLE WILL BE LOGGED AND CALIPERED, CEMENT USED TO BE 50% OVER CALIPER AND WILL BE CIRCULATED TO SURFACE. APPROVED	Subsequent Report		
APPROVED Altering Casing Other Dispose Water (Note: Report results of multiple completion on Englection Dispose Water (Note: Report results of multiple completion on Reports and Active Periposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally of give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* CHANGE ORIGINAL APD. FOR PRODUCTION CASING: FROM: 5½" CASING TO 4½" 10.5# J-55 8rd. TO BE CEMENTED WITH 827 CU. FT. LEAD CEMENT OF 65/35 POSMIX CONSISTING OF 6% CEL., 2% CA. CL. + 4# SX. OF PERLITE, FOLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 2% CA. CL. TOTAL CEMENT 945 CU. FT. 7-5/8" HOLE WILL BE LOGGED AND CALIPERED, CEMENT USED TO BE 50% OVER CALIPER AND WILL BE CIRCULATED TO SURFACE. APPROVED Thereby cepto, that the foregoing is true and correct			
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally of give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* CHANGE ORIGINAL APD. FOR PRODUCTION CASING: FROM: 5½" CASING TO 4½" 10.5# J-55 8rd. TO be CEMENTED WITH 827 CU. FT. LEAD CEMENT OF 65/35 POSMIX CONSISTING OF 6% Gell, 2% CA. CL. + 4# SX. OF PERLITE, FOLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 2% CA. CL. TOTAL CEMENT 945 CU. FT. 7-5/8" HOLE WILL BE LOGGED AND CALIPERED, CEMENT USED TO BE 50% OVER CALIPER AND WILL BE CIRCULATED TO SURFACE. APPROVED	Final Abandonment Notice		
CHANGE ORIGINAL APD. FOR PRODUCTION CASING: FROM: 5½" CASING TO 4½" 10.5# J-55 8rd. TO BE CEMENTED WITH 827 CU. FT. LEAD CEMENT OF 65/35 POSMIX CONSISTING OF 6% GEL, 2% CA. CL. + 4# SX. OF PERLITE, FOLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 2% CA. CL. TOTAL CEMENT 945 CU. FT. 7-5/8" HOLE WILL BE LOGGED AND CALIPERED, CEMENT USED TO BE 50% OVER CALIPER AND WILL BE CIRCULATED TO SURFACE. 1 hereby ceptor, that the foregoing is true and correct	· ·		
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally of give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* CHANGE ORIGINAL APD. FOR PRODUCTION CASING: FROM: 5½" CASING TO 4½" 10.5# J-55 8rd. TO be CEMENTED WITH 827 CU. FT. LEAD CEMENT OF 65/35 POSMIX CONSISTING OF 6% GEL, 2% CA. CL. + 4# SX. OF PERLITE, FOLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 2% CA. CL. TOTAL CEMENT 945 CU. FT. 7-5/8" HOLE WILL BE LOGGED AND CALIPERED, CEMENT USED TO BE 50% OVER CALIPER AND WILL BE CIRCULATED TO SURFACE. APPROVED APPROVED			(Note: Report results of multiple completion on Well
. I hereby ceptity that the foregoing is true and correct APPROVED	FROM: 5½" CASING TO 4½" 10.5# TO BE CEMENTED WITH 827 CU. FT 6% CEL, 2% CA. CL. + 4# SX. OI 118 CU. FT. + 2% CA. CL. TOTAI 7-5/8" HOLE WILL BE LOGGED AND	J-55 8rd. I. LEAD CEMENT OF 65/35 POSMIX CONSIST PERLITE, FOLLOWED WITH 100 SX. REG. L CEMENT 945 CU. FT. D CALIPERED, CEMENT USED TO BE 50% OVE	NEAT OL COM. ON
Signed Signed Signed Supervisor Date October 1, 19	1) E Mark to	Title Area Supervisor	APPROVED Date October 1, 1990
	8		

(This space for Federal or State office use) 1990 Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United State or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side