

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1445' FSL 1295' FWL, Sec. 32, T-32-N, R-8-W, NMPM, San Juan County

API # (assigned by OCD)

30-045-28566

5. Lease Number

6. State Oil&Gas Lease #

K-5808-NM

7. Lease Name/Unit Name

Albino Canyon

8. Well No.

#101

9. Pool Name or Wildcat

Basin Fruitland Coal

10. Elevation:

Type of Submission

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment

Type of Action

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

It is intended to install a pump in the subject well according to the attached procedure and wellbore diagram.

SIGNATURE [Signature] (DWM) Regulatory Administrator March 30, 1999

TLW

(This space for State Use)

Approved by

ORIGINAL SIGNED BY CHARLIE T. PETERSON Title

DEPUTY OIL & GAS INSPECTOR, DIST. #3

Date

MAR 31 1999

Albino Canyon #101
PUMPING UNIT INSTALLATION PROCEDURE

Unit K, Section 36, T32N-R8W, San Juan County, New Mexico

Lat. 36.936610 / 36° 56.20'

Long. 107.630860 / 107° 37.85'

1. MIRU pulling unit.
2. NDWH / NUBOP. Kill if necessary with produced Fruitland coal water.
3. PU 1 joint of tubing. TIH to tag for fill.
4. TOH standing back 2-3/8" tubing. (Tubing is set @ 3846', there are 123 jts of 2-3/8" 4.7# J-55 with an "F" nipple @ 3813').
5. PU 3-7/8" bit on tubing and TIH to PBTD. Circ hole clean. (Note: COTD is @ ~3857').
6. TIH w/ 2-3/8" tubing string and land tubing @ 3852'. Purge valve will be on bottom followed by pup joint, perforated sub, and standard seating nipple. Space out as needed with pup joints.
7. Hang tubing in donut. NDBOP / NUWH.
8. TIH w/ new 1.25" top hold down pump, 3/4" Grade D sucker rods (w/ spray metal couplings), polished rod, and polished rod liner. (Note: Vendor contact is listed below).
9. Seat the downhole pump, hang horses head, and space out pump.
10. Load tubing, and pressure test.
11. Start pumping unit and test (adjust spacing if needed).
12. RDMO.

COMPLY WITH ALL FEDERAL, STATE AND LOCAL RULES AND REGULATIONS RELATING TO OIL AND GAS OPERATIONS.


Prepared: D.W. Mussett

 323.99
Approved: Drilling Supt.

Pump Vendor: Energy Pump
Leo Noyes 564-2874

Albino Canyon #101
March 18, 1999
Basin Fruitland Coal
Unit K, Section 36, T32N, R8W, San Juan County, New Mexico

Completed: 11/16/91

