

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-045-28658
3. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name San Juan 32-7 Unit
8. Well No. 224
9. Pool name or Wildcat BASIN FRUITLAND COAL

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	
2. Name of Operator PHILLIPS PETROLEUM COMPANY	
3. Address of Operator 5525 HWY 64 NBU 3004, FARMINGTON, NM 87401	
4. Well Location Unit Letter N : 1294 Feet From The South Line and 1407 Feet From The West Line Section 21 Township 32N Range 7W NMPM San Juan County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6340' GL	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: 7" Csg <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-2-92

Four Corners #6 ran 7", 23#, K-55 casing and set @ 2938'. Cemented w/415 Sx 65/35 Poz w/12% gel and 1/4#/sk Flocele followed by 150 Sx Class B with 25#/sk Flocele. Bumped plug w/1500 psi. (Circ 119 bbls cement) WOC 4 hrs. ND BOP's and NU WH. RD and released rig @ 1800 hrs on 9-2-92.

415  
150  
565

RECEIVED

OCT 02 1992

OIL CON. DIV.  
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE R. A. Allred TITLE Drilling Supervisor DATE 9-29-92  
TYPE OR PRINT NAME R. A. Allred TELEPHONE NO.

(This space for State Use)

APPROVED BY Original Signed by FRANK I. CHAVEZ TITLE SUPERVISOR DISTRICT # 3 DATE OCT 02 1992  
CONDITIONS OF APPROVAL, IF ANY: