

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

2200' FNL 870' FEL, Sec.33, T-31-N, R-9-W, NMPM

5. Lease Number

SF-078439

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number

Johnston Federal #22R

9. API Well No.

30-045-28848

10. Field and Pool

Basin Fruitland Coal

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Notice of Intent
 Subsequent Report
 Final Abandonment

Type of Action

Abandonment
 Recompletion
 Plugging Back
 Casing Repair
 Altering Casing
 Other -
 Change of Plans
 New Construction
 Non-Routine Fracturing
 Water Shut off
 Conversion to Injection

13. Describe Proposed or Completed Operations

It is intended to install a pump in the subject well according to the attached procedure and wellbore diagram.

14. I hereby certify that the foregoing is true and correct.

Signed *John E. J. (EJG)* Title Regulatory Administrator Date 1/21/99
TLW

(This space for Federal or State Office use)

APPROVED BY /s/ Duane W. Spencer Title Team Lead, Petroleum Management FEB 19 1999

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Johnston Federal #22R
PUMPING UNIT INSTALLATION PROCEDURE
1/13/99

Unit H, Section 33, T31N, R9W, San Juan County, New Mexico
Aircare Lat. 36 51.35'
Aircare Long. 107 46.77'

1. MIRU PULLING UNIT.
2. BLOW DOWN TBG. KILL WELL W/ WATER ONLY IF NECESSARY.
3. NDWH / NUBOP.
4. PU 1 JT. OF TBG. - TIH TO TAG FOR FILL.
5. TOH STANDING BACK 2-3/8" TBG. (TBG. IS SET @ 3002', THERE ARE 95 JTS. OF 2-3/8" 4.7# J-55 WITH SN @ 2970').
6. PU 4-3/4" BIT ON TBG. AND TIH TO COTB, CIRC. HOLE CLEAN. TOH W/ SAME.
7. TIH W/ 2-3/8" TBG. STRING AND LAND TBG. @ 2991'. PURGE VALVE WILL BE ON BOTTOM W/ 2-3/8"x10' PUP JOINT(2981'-2991'), 2-3/8"x6' PUP JOINT(2975'-2981'), 2-3/8"x4' PERFORATED SUB(2971'-2975') AND 2-3/8" SN @ 2971'.
8. HANG TBG. IN DONUT. NDBOP / NUWH.
9. TIH W/ NEW TOP HOLD DOWN ROD PUMP (2"x1-1/4"x10'x14' RHAC-Z), 4' SECTION CUP TYPE PLUNGER. RUN THREE - 1-1/4" SINKER BARS, APPROX. 100 - 3/4" GRADE D SUCKER RODS (W/ SPRAY METAL COUPLINGS), A SET OF 3/4" PONY RODS (2' .4' .6' .8') TO SPACE OUT, ONE - 1-1/4"x 22 - 3/4" PIN POLISHED ROD AND ONE - 1/1/4"x1-1/2"x10' POLISHED ROD LINER.
10. SEAT THE DOWNHOLE PUMP, HANG HORSES HEAD ON, SPACE PUMP.
11. LOAD TBG. . PRESSURE TEST.
12. START PUMPING UNIT, AND TEST OK (ADJUST SPACING IF NEEDED).
13. RDMO.

COMPLY WITH ALL FEDERAL, STATE AND LOCAL RULES AND REGULATIONS RELATING TO OIL AND GAS OPERATIONS.

E.J. Giles 1-13-99

Prepared: E.J. Giles
Office: 326-9584
Home: 325-8164
Pager: 324-2636

Bruce V. Bony 1-14-99
Approved: Drilling Supt.

Johnston Federal #22R
(Current)
Basin Fruitland Coal
Unit H, Section 33, T31N, R9W, San Juan County, New Mexico

Completed: 12/17/92
 Recavitated: Sep-98

