

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: September 30, 1990

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well ☐ Oil Well ☒ Gas Well ☐ Other	5. Lease Designation and Serial No. SF078097
2. Name of Operator SG Interests I, Ltd.	6. If Indian, Allottee or Tribe Name -
3. Address and Telephone No. P. O. Box 421, Blanco, NM 87412-0421 (505) 325-5599	7. If Unit or CA, Agreement Designation -
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1360' FNL & 950' FEL Section 28, T31N, R11W	8. Well Name and No. Federal 31-11-28 #1
	9. API Well No.
	10. Field and Pool, or Exploratory Area Basin Fruitland Coal
	11. County or Parish, State San Juan County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
☐ Notice of Intch	☐ Abandonment
☒ Subsequent	☐ Recompletion
☐ Final Abandonment Notice	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☒ Other
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Fracturing
	☐ Water Shut-Off
	☐ Conversion to Injection

Production Casing
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is discontinuously drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Production Casing: TD @ 2560' on 12-06-92.
Hole Size: 7 7/8"
Casing: 66 Jts (2543.70') 5 1/2", 15.5#, J-55, LT&C, Casing set @ 2555.70', Guide Shoe @ 2555', Float Collar @ 2512.16', 12 Centralizers @ 2536', 2494', 2410', 2326', 2242', 2158', 2074', 1990', 1906', 1822', 1738', & 1654'.
Cement: 10 bbls Scavenger + 215 sx Class B 65/35 Poz w/12% gel 5 pps Hi-Seal & 1/4 pps Cello-Seal (2.93 Yield/632 cu ft) + 100 sx Class B w/1% CF-14 & 0.4% Thrifty Lite (1.18 Yield/118 cu ft). Circ 4.5 bbls cement to surface.
Bump Plug w/1250 psi.
Plug Down @ 12:30 PM on 12-07-92.

14. I hereby certify that the foregoing is true and correct

Signed Carrie Bay Title Agent (915) 694-6106 Date 12/10/92

(This space for Federal or State office use)

Approved by _____ Title _____ Date _____
Conditions of approval, if any:

NMOC