

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

Santa Fe, New Mexico 87504-2088

RECEIVED
DEC 17 1993
OIL CON. DIV

WELL API NO.	3004528953
5. Indicate Type of Lease	STATE ☒ FEE ☐
6. State Oil & Gas Lease No.	SF-078604-A
7. Lease Name or Unit Agreement Name	Martinez Gas Com J
8. Well No.	#1
9. Pool name or Wildcat	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL ☐ GAS WELL ☒ OTHER ☐	2. Name of Operator Amoco Production Company	Attention: Julie L. Acevedo
3. Address of Operator P.O. Box 800 Denver Colorado 80201	4. Well Location Unit Letter K : 1760 Feet From The South Line and 1720 Feet From The West Line Section 32 Township 32N Range 10W NMPM San Juan County	
10. Elevation (Show whether DF, RKB, RT, OR, etc.)		

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☐
OTHER: ☐	CASING TEST AND CEMENT JOB ☐
	OTHER: Spud and Set ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud a 17-1/2" surface hole on 10/29/93 at 5:00 hrs. Drilled to 400'.
Set 13.375 61" J-55 surface casing at 392'. Cemented with 7803X CL B. Circulated 300 SK to the surface.
Pressure tested casing to 1500 psi. Drilled a 12.250" hole to a depth of 3268' on 11/16/93. Set 9.625" 36" J-55 intermediate casing at 3265'. Cemented with 1st string 250SK CL G, 2nd string 1630SK Newco Lite, Tail w/ 100SK CL B. Circulated 80 BBLS to the surface. Pressure tested casing to psi.
Drilled a 8.750" hole to a depth of 7171' on 11/14/93. Set 7", 23", J-55 protective casing at 7165'. Cemented with 600SK CL B TOC @ 2950'.
Drilled a 6.25" hole to a TD depth of 7640' on 11/22/93. Set 4-1/2", 11.6 N80 Production Liner, Top at 6927', Bottom at 7640'. cemented with 60SK CL G TOC @ 6927'.
Rig released at 11/22/93 hrs. on 08:00.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE: Julie L. Acevedo TITLE: Sr. Staff Assistant DATE: 11-29-1993
TYPE OR PRINT NAME: Julie L. Acevedo TELEPHONE NO.: (303) 830-6003

(This space for State Use)

Original Signed by FRANK T. CHAVEZ

APPROVED BY: TITLE: DATE: 3-17-93

CONDITIONS OF APPROVAL, IF ANY:

SUPERVISOR DISTRICT # 3