

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well

Pressure Observation Well

2. Name of Operator

MERIDIAN OIL

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1775' FSL, 905' FEL Sec. 19, T-32-N, R-6-W, NMPM

5. Lease Number

SF-081155

6. If Indian, All. or

7. Unit Agreement Name

Allison Unit

8. Well Name & Number

Allison Unit POW 2

9. API Well No.

30-045-29004

10. Field and Pool

Basin Ft Coal

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Subsequent Report☐ Recompletion☐ New Construction☐ Final Abandonment☐ Plugging Back☐ Non-Routine Fracturing☐ Casing Repair☐ Water Shut off☐ Altering Casing☐ Conversion to Injection☒ Other -

13. Describe Proposed or Completed Operations

11-17-93 TD 252'. Spud @ 10:15 p.m. 11-17-93. Drl surface hole. Ran 5 jts 8 5/8", 24.0#, K-55 ST&C csg, 233' set @ 252'. Cmt w/235 sx Class "B" w/2% calcium chloride and 0.25 pps flocele (278 cu.ft.), circ 15 bbl to surface.

11-23-93 TD 3643'. Ran 84 jts 4 1/2", 10.5#, K-55 ST&C csg, 3631' set @ 3643'. Stage tool @ 2855'. Cmt first stage w/45 sx Class "B" 65/35 Poz w/6% gel, 2% calcium chloride, 0.25 pps flocele and 3 pps gilsonite (80 cu.ft.), tail w/100 sx Class "B" w/2% calcium chloride (118 cu.ft.), circ 14 bbl cmt to surface. Cmt second stage w/626 sx Class "B" 65/35 Poz w/2% calcium chloride, 0.25 pps flocele and 6% gel (1108 cu.ft.). Circ 20 bbl cmt to surface. PT 3800 psi, ok.

14. I hereby certify that the foregoing is true and correct.

Signed

Title Regulatory Affairs

Date 11/29/93

(This space for Federal or State Office use)

APPROVED BY

Title

Date

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

DEC 01 1993

FARMINGTON DISTRICT OFFICE

BY