

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. <u>30-045-29169</u>
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL ☐ GAS WELL ☒ OTHER	7. Lease Name or Unit Agreement Name <u>LA PLATA 4</u>
2. Name of Operator <u>Texa Koma Oil & Gas Corporation (214) 701-9106</u>	8. Well No. <u>1</u>
3. Address of Operator <u>ONE LINCOLN Centre, 5400 LBJ FREEWAY, STE 500 TX DALLAS, 75240</u>	9. Pool name or Wildcat <u>(71629) BASIN Fruitland Coal</u>
4. Well Location Unit Letter <u>K</u> : <u>2480</u> Feet From The <u>South</u> Line and <u>2215</u> Feet From The <u>WEST</u> Line Section <u>4</u> Township <u>31N</u> Range <u>13W</u> NMPM <u>San Juan</u> County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) <u>5909' GLM</u>

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☐
OTHER: <u>update</u> ☒	PLUG AND ABANDONMENT ☐
	CASING TEST AND CEMENT JOB ☐
	OTHER: <u>Completion</u> ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.
ON 09/18/95 RAN CBL/CCL/GR FROM 2177' PBTD (FLOAT SHOE) TO SURFACE CASING SHOE @ 130' AND PERFORATED W/19 GPS, 0.45" DIAMETER HOLE SIZE THE FOLLOWING INTERVALS: 2086'-88'(2' @ 4 SPF, 90 DEG PHASE), 2078'-82'(4' @ 4 SPF, 90 DEG PHASE), 2059'-76'(17' @ 4 SPF, 90 DEG PHASE), 2048'-57'(9' @ 4 SPF, 90 DEG PHASE), 1972'-74'(2' @ 2 SPF, 180 DEG PHASE), 1957'-64'(7' @ 2 SPF, 180 DEG PHASE), 1951'-55'(4' @ 2 SPF, 180 DEG PHASE), 1844'-50'(6' @ 1 SPF, 0 DEG PHASE), AND 1840'-42'(2' @ 1 SPF, 0 DEG PHASE). FRAC'ED W/70% QUALITY FOAM W/138 M LBS SAND. SET 2 3/8", 4.7 PPF, R-2, EUE, 8rd, J-55, USED, TBG @ 1825' GLM EOT, SN @ 1792'; PACKERLESS COMPLETION. LAID FLOWLINE, SET SURFACE EQUIPMENT, PUT WELL ON PUMP.

RECEIVED
OCT 12 1995

OIL CON. DIV.
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Walter J. Toups Jr. TITLE Drilling Manager DATE 10-05-95
TYPE OR PRINT NAME Walter J. Toups Jr. TELEPHONE NO. (214) 701-9106

(This space for State Use)

APPROVED BY Original Signed by FRANK T. CHAVEZ SUPERVISOR DISTRICT 10 DATE OCT 12 1995

CONDITIONS OF APPROVAL, IF ANY: