

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

**DISTRICT I**

P.O. Box 1980, Hobbs NM 88240

**DISTRICT II**

P.O. Drawer DD, Artesia, NM 88210

**DISTRICT III**

1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-045-29359
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	E-178-4
7. Lease Name or Unit Agreement Name	San Juan 32-7 Unit 009260
8. Well No.	#13A
9. Pool name or Wildcat	Blanco Mesaverde 72319

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	
2. Name of Operator Phillips Petroleum Company	
3. Address of Operator 5525 Highway 64, NBU 3004, Farmington, NM 87401	
4. Well Location Unit Letter <u>E</u> : <u>1546'</u> Feet From The <u>North</u> Line and <u>826'</u> Feet From The <u>West</u> Line Section <u>16</u> Township <u>32N</u> Range <u>7W</u> NMPM <u>San Juan</u> County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) <u>6652'</u>	

11.

**Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data**

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: spud report ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-2-96  
MI & RU Big A 32. Spud 12-1/4" hole @ 1600 hrs on 5-2-96. Drilled to 357'. RU Casing Crew & RIH w/9-5/8", 36# K-55 ST&C casing to @ 357'. Cemented 9-5/8" casing with 170 sx C1 B + 2% CaCl + 1/4#/sx celloseal, 37 bbl slurry @ 15.6 ppg, 1.15ft3/sx yield. Displaced plug w/24.5 bbls. Plug down @ 0348 hrs. Circ. 97 sx to surf. WOC 4 hours. NU BOP. Test BOP - OK

**RECEIVED**  
MAY - 7 1996  
**OIL CON. DIV.**  
DIST. 2

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ed Hasely TITLE Envir./Regulatory Engineer DATE 5-6-96  
TYPE OR PRINT NAME Ed Hasely TELEPHONE NO. 505-599-3460

(This space for State Use)

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT # 2 DATE MAY - 7 1996  
CONDITIONS OF APPROVAL, IF ANY: