

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Highway 64, NBU 3004, Farmington, NM 87401

505-599-3454

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit D, 1189' FNL & 864' FWL
Section 22, T32N, R7W

5. Lease Designation and Serial No.

SF-078459

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 32-7 Unit

8. Well Name and No.

SJ 32-7 #32A

9. API Well No.

30-045-29364

10. Field and Pool, or exploratory Area

Blanco Mesaverde

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other 7" casing
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

RIH and tagged cement @ 301'. Drill cement then formation (8-3/4" hole) to 4124'. RIH and set 7", 20# J-55 ST&C 8rd casing at 4125'. Cemented lead w/470 sx 65/35 POZ + 10% gel + 2% CaCl2 + 1/4#/sx celloseal mixed at 12.1 ppg and 2.02 ft3/sx; tail - 100 sx Class B + 2% gel + 1/4#/sx celloseal mixed at 15.6 ppg and 1.20 ft3/sx. Did not circulate cement to surface. WOC. ND BOP, set slips. NU BOP. Run Temperature Survey. Top of Cement at 790'. Test BOP - OK. (Danny Jaap discussed TOC w/Errol Beecher w/BLM at 1920 hrs 4-28-96. BLM requires cement 50' above top of Nacimiento. Top of Nacimiento est. 1330'. No need for remedial work since TOC above 1200').

14. I hereby certify that the foregoing is true and correct

Signed E. J. Haseley

Title Envir./Regulatory Engineer

Date 5-3-96

(This space for Federal or State office use)

Approved by _____

Title _____

Conditions of approval, if any: _____

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

NMOC

FARMINGTON DISTRICT OFFICE
BY E. J. Haseley