

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
Pressure Observation Well

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1155' FNL, 1720' FWL, Sec. 24, T-32-N, R-10-W, NMPM

5. Lease Number

SF-078504

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 32-9 Unit

Well Name & Number

San Juan 32-9 U POW #1

9. API Well No.

30-045-29381

10. Field and Pool

Basin Fruitland Coal

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

☒ Other -

13. Describe Proposed or Completed Operations

11-23-96 Core #1: 3525-3555', cut 30', recovered 30'. TOOH.

11-24-96 Drill @ 3555-3708'. Circ hole clean. TOOH. TIH. Core #2: 3708-3721', cut 13', recovered 13'. TOOH.

11-25-96 TIH. Core #3: 3721-3728', cut 7', recovered 7'. Circ hole clean. TOOH. Drill from 3728 to @ TD 3795'. Circ hole clean. TOOH. Ran logs.

11-26-96 TOOH. TIH, circ hole clean. Pump 20 sx Class "B" neat cmt @ 3387'.

TOOH. TIH w/81 jts 7" 23# K-55 csg, set @ 3346'. Circ csg clean. Pump wtr ahead. Pump 40 bbl pre-flush, wtr ahead. Cmt d w/406 sx Class "B" 65/35 poz. Tailed w/100 sx Class "B" cmt. Circ 30 bbl pre flush to surface. ND BOP.

11-27-96 PT secondary seal to 1500 psi/15 min, OK. NU BOP. TIH, tag cmt @ 3310'. SD for holiday.

11-29-96 TOOH. TIH, ran CBL-GR @ 100-3268'. Cmt intervals: 2170-3268', 95-100% bond; 1730-2170', 85-95% bond; 930-1730', 50-85% bond; 380-930', 50-70% bond; 350-380', 20-50% bond. TOC @ 350'. TOOH. TIH, drill cmt @ 3310-3346'. CO to 3728'. Circ hole clean. Blow well & CO.

11-30-96 Blow well & CO.

12-1-96 Blow well & CO.

12-2-96 TOOH. TIH w/12 jts 4 1/2" 10.5# J-55 ST&C lnr, set @ 3720'. Top of lnr @ 3192'. TOOH. ND BOP. NU WH. RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 12/5/96

(This space for Federal or State Office use)

APPROVED BY

Title

Date

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

DEC 06 1996

FARMINGTON DISTRICT OFFICE

BY

NMOCD