

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.	3004529402
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil / Gas Lease No.	
7. Lease Name or Unit Agreement Name	NEW MEXICO STATE COM DY
8. Well No.	1
9. Pool Name or Wildcat	BLANCO - MESA VERDE
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 5943'	

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMITS"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator  
FOUR STAR OIL AND GAS COMPANY

3. Address of Operator 3300 N. Butler Ave., Suite 100 Farmington NM 87401

4. Well Location  
Unit Letter D : 805 Feet From The NORTH Line and 810 Feet From The WEST Line  
Section 36 Township T31N Range R12W NMPM SAN JUAN COUNTY

10. Elevation (Show whether DF, RKB, RT, GR, etc.) 5943'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPERATION ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: T.D. & PRODUCTION CASING ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

FOUR STAR OIL & GAS COMPANY HAS COMPLETED THE FOLLOWING ON THE SUBJECT WELL:

10/5/96 - DRILL 7-7/8" HOLE TO 5064' (T.D.) CIRCULATE HOLE TO LOG. RUN DEN/CNL/GR, DIL FROM 5063' TO BASE OF SURFACE CASING.

RUN 115 JTS. 4-1/2", 11.6#, K-55 CASING. SET AT 5064'. CEMENT WITH (LEAD) 582 SX (1100 CU. FT.) 35/65 POZMIX CLASS 'G' CEMENT WITH 6 % GEL, 10# / SX GILSONITE, 2% CaCl, 1/4 # / SX FLOCELE. 12.6 PPG & 1.89 CU. FT. / SX. FOLLOWED BY (TAIL) 1029 SX (1255 CU. FT.) 50/50 POZMIX CLASS 'G' CEMENT WITH 2% GEL, 5# / SX GILSONITE, 2% CaCl, 1/4 # / SX FLOCELE. 14.0 PPG & 1.22 CU. FT. SX.

COULD NOT BUMP PLUG, PSI UP TO 4100 PSI. ND BOP. CUT OFF 4-1/2" CASING. WELD ON CASING HEAD. RELEASE RIG AT 2:15 A.M. 10/6/96. EVALUATE FOR COMPLETION.

**RECEIVED**  
OCT - 8 1996  
**OIL CON. DIV.**  
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ted A. Tipton TITLE Operating Unit Manager

DATE 10/7/96

TYPE OR PRINT NAME Ted A. Tipton

Telephone No. 325-4397

(This space for State Use)

APPROVED Johnny Robinson  
CONDITIONS OF APPROVAL, IF ANY: DEPUTY OIL & GAS INSPECTOR, DIST. #3

DATE OCT - 8 1996