

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

DISTRICT I
P.O. Box 1980, Hobbs NM 88241-1980

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.
30-045-29546

Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

017654

San Juan 32-7 Unit

009260

2. Name of Operator

Phillips Petroleum Company

8. Well No.

SJ 32-7 Unit #241

3. Address of Operator

5525 Highway 64, NBU 3004, Farmington NM 87401

9. Pool name or Wildcat

Basin Fruitland Coal

71629

4. Well Location

Unit Letter G : 2234' Feet From The North Line and 1841' Feet From The East Line

Section 21 Township 32N Range 7W NMPM San Juan County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Spud Report ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3/26/99

MIRU Key Energy #53. Spud 12-1/4" hole @ 1500 hr 3/27/99. Drilled to 375'. Circulated hole. RIH w/9-5/38" 36#, J-55 casing & set @ 373'. RU BJ to cement. Pumped 10 bbls mud clean and 10 bbls water ahead of 185 sx C1 H w/2% CaCl2 and 1/4#/sx Celloflake mixed at @ 15.6 ppg w/1.20 cf/sx yield. Displace wood plug with 25 bbls water. Circulated 10 bbls (56 cf) cement to surface. Plug down 0852 hrs 3/28/99. WOC. NU WH & NU BOP. PT manifold and casing to 200 psi for 3 minutes and 1500 psi for 10 min. Held OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Patsy Clugston

TITLE

Regulatory Assistant

DATE

3/29/99

TYPE OR PRINT NAME

Patsy Clugston

TELEPHONE NO. 505-599-3454

(This space for State Use)

ORIGINAL SIGNED BY CHARLIE T. PERRIN

DEPUTY OIL & GAS INSPECTOR, DIST. #3

APPROVED BY

TITLE

MAR 31 1999

CONDITIONS OF APPROVAL, IF ANY: