Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED					
Budget Bureau	No.	100	4-0135		
Expires: M	arch 3	1.	1993		

	Expires:	March 31	, 1993
5.	Lease Designa	tion and Se	rial No.

SF-079329 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT - " for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE San Juan 32 Fed 12 1. Type of Well 8. Well Name and No. Oil Wel X Gas 2. Name of Operator SJ 32 Fed 12 #1 Phillips Petroleum Company 9. API Well No. 3. Address and Telephone No. 30-045-29762 505-599-3454 5525 Highway 64, NBU 3004, Farmington, NM 87401 10. Field and Pool, or exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Basin Fruitland Coal Unit M. 1078' FSL & 1226' FWL 11. County or Parish, State Section 12, T32N, R9W San Juan. NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Notice of Intent Abandonment New Construction Recompletion Subsequent Report Non-Routine Fracturing Plugging Back Water Shut-Off Casing Repair Final Abandonment Notice Conversion to Injection Altering Casing Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1. Time Completed: 1735 hrs Date: 9/5/99 Time Started: 1630 hrs Hole: 8-3/4" Casing Size: 7", 20#, K-55 New; Casing Set 33381 Turbo Centralizers at 3327', 3292', 3251', 3168', 3084' 3003', 378'. Spring Type Centralizers____ 2253', 2216' 2295', _ Mud Flush 10 bbls, Spacer 10 Fresh Water. Stage 1: Lead Slurry: 420 sx (829 cf) 35/65 Class H POZ w/5#/sx Gilsonite, 1/4# sx Cello-flake, 6% ge Mixed at 12.0 ppg, a yield of 2.10. Tail Slurry: 100 sx (127.5 cf) Class H cement w/5#/sx Gilsonite, 1/4#/sx Cello-flake, 0.3% FL-52, 2% CaCl2 mixed at 15.2 ppg, a yield of 1.28. Stage 2: Lead Slurry: ____ Tail Slurry: 8 bbls/sacks 21 Displaced Plug with 133.5 bbls fresh water. Volume Cement Circulated Average Pressure 112 psi, Average Rate 5 bpm, Bumped plug with 1400 psi. 14. I hereby Regulatory Assistant (This space for Federal or State office use) ACCEPTED FOR RECORD Approved by . Title Conditions of approval, if any: Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States Figure 1 (1) and the Company of the United States Fig

* See Instruction on Reverse Side

or representations as to any matter within its jurisdiction.

FARMINGTON FIELD OFFICE