

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals.

SUBMIT IN TRIPLICATE

SEP - 1 1999

OIL CON. DIV.
DIST. 3

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Highway 64, NBU 3004, Farmington, NM 87401 505-599-3454

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit M, 958' FSL & 1055' FWL
Section 24, T32N, R9W

5. Lease Designation and Serial No.

SF-079329

6. If Indian, Allottee or Tribe Name

7. Unit or CA, Agreement Designation

San Juan 32 Fed 24

8. Well Name and No.

SJ 32 Fed 24 #2

9. API Well No.

30-045-29789

10. Field and Pool, or exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other 7" casing report

- ☐ Change of Plans
☐ New Construction
☐ Non-Routing Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

RIH w/8-3/4" bit & tagged cement @ 340'. Drilled cement from 340' to 380'. Drilled new formation to 3394'. Circ. hole. COOH. RIH w/7" 20#, K-55 casing and set @ 3391'. RU BJ to cement. Pumped 10 bbls mud clean, 10 bbls FW w/dye. Then pumped lead slurry - 395 sx (829 cf) 35/65 Class H POZ w/5#/sx Gilsonite, 1/4#/sx Cello-flake, 6% Gel, mixed at 12.0 ppg, a yield of 2.10. Tail slurry - 100 sx (127.5 cf) Class H cement w/5#/sx Gilsonite, 1/4#/sx Cello-flake, 0.3% FL-52, 2% CaCl2 mixed at 15.2 ppg, a yield of 1.28. Dropped plug and displaced w/135 bbls FW with additional displacement of 1.5 bbls. Plug not bumped. Pressured to 900 psi. Bled back 1/2 bbl & float held. Had 10 bbls (56 cf) cement circulated to surface. WOC. RD BJ.

ND BOP & set slips & cut off casing. NU WH. PT casing, rams and manifold to 200 psi for 3 minutes and 1800 psi for 10 minutes. Good test.

14. I hereby certify that the foregoing is true and correct.

Signed

Patsy Clugston

Title

Regulatory Assistant

Date

8/17/99

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

RMOC

FARMINGTON FIELD OFFICE
BY *[Signature]*