

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

Sundry Notices and Reports

99 JUL 19 PM 1:03

1. Type of Well
GAS

070 FARMINGTON, NM

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

RECEIVED
JUL 26 1999

OIL CON. DIV.
DIST. 3

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

2535' FNL 400' FWL, Sec. 20, T-32-N, R-9-W, NMPM

5. Lease Number
NM-58887

6. If Indian, All. or
Tribe Name

Unit Agreement Name

8. Well Name & Number
Newco #1A

9. API Well No.
30-045-29801

10. Field and Pool
Blanco Mesaverde

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent	☐ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☒ Other - Casing & cement	

13. Describe Proposed or Completed Operations

6-30-99 Drill to intermediate TD @ 3845'. Circ hole clean. TOOH.

7-1-99 TIH w/5 jts 7" 23# N-80 LT&C csg & 86 jts 7" 20# J-55 ST&C csg, set @ 3836'. Cmdt w/450 sx Class "B" neat cmt w/3% Econolite, 0.5 pps Flocele, 10 pps Gilsonite (1310 cu ft). Tailed w/90 sx Class "B" 50/50 poz cmt w/2% gel, 2% calcium chloride, 10 pps Gilsonite, 0.5 pps Flocele (128 cu ft). Circ 8 bbls cmt to surface. WOC. NU BOP. PT BOP & csg to 1500 psi/30 min, OK. Drilling Ahead.

7-3-99 Drill to TD @ 6350'. Circ hole clean. TIH w/61 jts 4 1/2" 10.5# J-55 ST&C csg set @ 6334'. Lnr top @ 3613'. Cmdt w/290 sx Class "H" 50/50 POZ cmt w/2% gel, 0.5% Halad-344, 0.25 pps Flocele, 5 pps Gilsonite, 0.1% HR-5 (406 cu ft). Circ 14 bbls cmt to surface.

7-4-99 ND BOP. NU WH. RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 7/8/99

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC

ACCEPTED FOR RECORD
JUL 22 1999
FARMINGTON FIELD OFFICE
BY [Signature]

January 18, 1999

OPERATIONS PLAN

Well Name: Newco #1A
Location: 2535' FNL, 400' FWL, Sec 20, T-32-N, R-9-W
 San Juan County, NM
 Latitude 36° 58.2, Longitude 107° 48.6
Formation: Blanco Mesa Verde
Elevation: 6748'GR

<u>Formation Tops:</u>	<u>Top</u>	<u>Bottom</u>	<u>Contents</u>
Surface	San Jose	2132'	
Ojo Alamo	2132'	2171'	
Kirtland	2171'	2988'	
Fruitland	2988'	3575'	
Pictured Cliffs	3575'	3716'	
Lewis	3716'	4307'	
Intermediate TD	3816'		
Mesa Verde	4307'	4772'	
Chacra	4772'	5562'	
Massive Cliff House	5562'	5605'	
Menefee	5605'	5938'	
Massive Point Lookout	5938'	6267'	
Mancos Shale	6267'		
TD	6338'		

Logging Program:

Cased hole logging - Gamma Ray, Neutron - surface to TD
 Coring/DST - none

Mud Program:

<u>Interval</u>	<u>Type</u>	<u>Weight</u>	<u>Vis.</u>	<u>Fluid Loss</u>
0- 200'	Spud	8.4-9.0	40-50	no control
200-3816'	LSND	8.4-9.0	30-60	no control
3816-6338'	Gas	n/a	n/a	n/a

Pit levels will be visually monitored to detect gain or loss of fluid control.

Casing Program (as listed, the equivalent, or better):

<u>Hole Size</u>	<u>Depth Interval</u>	<u>Csq.Size</u>	<u>Wt.</u>	<u>Grade</u>
12 1/4"	0' - 200'	9 5/8"	32.3#	H-40
8 3/4"	0' - 3816'	7"	20.0#	J-55
6 1/4"	3716' - 6338'	4 1/2"	10.5#	J-55

Tubing Program:

0' - 6338' 2 3/8" 4.70# EUE

BOP Specifications, Wellhead and Tests:Surface to Intermediate TD -

11" 2000 psi minimum double gate BOP stack (Reference Figure #1).
 After nipple-up prior to drilling out surface casing, rams and casing will be tested to 600 psi for 30 minutes.

BURLINGTON RESOURCES OIL & GAS COMPANY NEWCO #1A

2535' FNL & 400' FWL, SECTION 20, T32N, R9W, N.M.P.M.
SAN JUAN COUNTY, NEW MEXICO

APD MAP #1

500' NEW BLM CONSTRUCTION
140' SW/NW SECTION 20, T32N, R9W.
360' NW/SW SECTION 20, T32N, R9W.

