UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

/

	ls [] 1:21	
770 777	1900, NA 5.	Lease Number SF-078134
Type of Well GAS	6.	If Indian, All. or Tribe Name
	7.	Unit Agreement Name
Name of Operator BURLINGTON RESOURCES OTL 5 GAS COMPANY	000	
RESOURCES OIL & GAS COMPANDED IN Address & Phone No. of Operator	8.	Well Name & Number Pierce SRC #1B
PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	API Well No. 30-045-30012
4. Location of Well, Footage, Sec., T, R, M 680'FNL, 1980'FEL, Sec.30, T-31-N, R-10-W, NMPM	10.	Field and Pool Blanco Mesaverde
B	11.	County and State San Juan Co, NM
12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE	REPORT, OTHER	DATA
Type of Submission Type of Ac	ction	
Notice of Intent Abandonment	Change of Pl	
	New Construction Non-Routine	Tracturing
X Subsequent Report Plugging Back	Non-Routine Water Shut o	ff
Casing Repair Final Abandonment Altering Casing		
X Other - Spud, cas		,
13. Describe Proposed or Completed Operations		
13. Describe Proposed or Completed Operations 5-25-00 MIRU. Spud well @ 9:30 pm 5-25-00.	777/2 ib = 0 f	O# 22 2# MC_EO STEC
Describe Proposed or Completed Operations 5-25-00 MIRU. Spud well @ 9:30 pm 5-25-00. 5-26-00 Drill to 156'. Circ hole clean. TOOH.	FIH w/3 jts 9 5/	8" 32.3# WC-50 ST&C
Describe Proposed or Completed Operations 5-25-00 MIRU. Spud well @ 9:30 pm 5-25-00. 5-26-00 Drill to 156'. Circ hole clean. TOOH. 'Csq, set @ 146'. Cmtd w/150 sx Class	"B" neat cmt w/	3% calcium chloride
Describe Proposed or Completed Operations 5-25-00 MIRU. Spud well @ 9:30 pm 5-25-00. 5-26-00 Drill to 156'. Circ hole clean. TOOH. ' csg, set @ 146'. Cmtd w/150 sx Class 0.25 pps cellophane (177 cu ft). Circ	"B" neat cmt wa c 10 bbl cmt to	3% calcium chloride
Describe Proposed or Completed Operations 5-25-00 MIRU. Spud well @ 9:30 pm 5-25-00. 5-26-00 Drill to 156'. Circ hole clean. TOOH. ' csg, set @ 146'. Cmtd w/150 sx Class 0.25 pps cellophane (177 cu ft). Circ PT BOP & csg to 600 psi/30 min, OK.	"B" neat cmt ware to bbl cmt to Drilling ahead.	3% calcium chloride surface. WOC. NU BO
Describe Proposed or Completed Operations 5-25-00 MIRU. Spud well @ 9:30 pm 5-25-00. 5-26-00 Drill to 156'. Circ hole clean. TOOH. ' csg, set @ 146'. Cmtd w/150 sx Class 0.25 pps cellophane (177 cu ft). Circ PT BOP & csg to 600 psi/30 min, OK. 1	"B" neat cmt wo c 10 bbl cmt to Drilling ahead. hole clean. TOO	3% calcium chloride surface. WOC. NU BO OH. TIH w/5 jts 7" 2
Describe Proposed or Completed Operations 5-25-00 MIRU. Spud well @ 9:30 pm 5-25-00. 5-26-00 Drill to 156'. Circ hole clean. TOOH. Completed of the second o	"B" neat cmt wong to bbl cmt to Drilling ahead. hole clean. TOO ST&C csg, set @	3% calcium chloride surface. WOC. NU BO OH. TIH w/5 jts 7" 2 2921'. Cmtd w/284 s:
Describe Proposed or Completed Operations 5-25-00 MIRU. Spud well @ 9:30 pm 5-25-00. 5-26-00 Drill to 156'. Circ hole clean. TOOH. ' csg, set @ 146'. Cmtd w/150 sx Class 0.25 pps cellophane (177 cu ft). Circ PT BOP & csg to 600 psi/30 min, OK. 5-28-00 Drill to intermediate TD @ 2930'. Circ N-80 ST&C csg, & 65 jts 7" 20# J-55 class "B" neat cmt w/3% sodium metal gilsonite (863 cu ft). Tail w/90 sx	"B" neat cmt w, c 10 bbl cmt to Drilling ahead. hole clean. TOO ST&C csg, set @ silicate, 0.25 pClass "B" 50/50	3% calcium chloride surface. WOC. NU BO 9H. TIH w/5 jts 7" 2: 2921'. Cmtd w/284 s: pps celloflakes, 5 p; poz w/2% calcium
Describe Proposed or Completed Operations 5-25-00 MIRU. Spud well @ 9:30 pm 5-25-00. 5-26-00 Drill to 156'. Circ hole clean. TOOH. Completed of the second o	"B" neat cmt w, c 10 bbl cmt to Drilling ahead. hole clean. TOO ST&C csg, set @ silicate, 0.25 pClass "B" 50/50	3% calcium chloride surface. WOC. NU BO 9H. TIH w/5 jts 7" 2: 2921'. Cmtd w/284 s: pps celloflakes, 5 p; poz w/2% calcium
Describe Proposed or Completed Operations 5-25-00 MIRU. Spud well @ 9:30 pm 5-25-00. 5-26-00 Drill to 156'. Circ hole clean. TOOH. Cosg, set @ 146'. Cmtd w/150 sx Class 0.25 pps cellophane (177 cu ft). Circ PT BOP & csg to 600 psi/30 min, OK. Solution of the complete of	"B" neat cmt w, c 10 bbl cmt to Drilling ahead. hole clean. TOO ST&C csg, set @ silicate, 0.25 pclass "B" 50/50 es, 5 pps gilson	3% calcium chloride surface. WOC. NU BOD OH. TIH w/5 jts 7" 2: 2921'. Cmtd w/284 s: ops celloflakes, 5 pp poz w/2% calcium nite (120 cu ft). Ci
Describe Proposed or Completed Operations 5-25-00 MIRU. Spud well @ 9:30 pm 5-25-00. 5-26-00 Drill to 156'. Circ hole clean. TOOH. csg, set @ 146'. Cmtd w/150 sx Class 0.25 pps cellophane (177 cu ft). Circ PT BOP & csg to 600 psi/30 min, OK. 5-28-00 Drill to intermediate TD @ 2930'. Circ N-80 ST&C csg, & 65 jts 7" 20# J-55 Class "B" neat cmt w/3% sodium metal gilsonite (863 cu ft). Tail w/90 sx chloride, 2% gel, 0.25 pps celloflak	"B" neat cmt w, c 10 bbl cmt to Drilling ahead. hole clean. TOO ST&C csg, set @ silicate, 0.25 pclass "B" 50/50 es, 5 pps gilson	3% calcium chloride surface. WOC. NU BO: OH. TIH w/5 jts 7" 2: 2921'. Cmtd w/284 s: ops celloflakes, 5 p: poz w/2% calcium nite (120 cu ft). Ci
Describe Proposed or Completed Operations 5-25-00 MIRU. Spud well @ 9:30 pm 5-25-00. 5-26-00 Drill to 156'. Circ hole clean. TOOH. Cosg, set @ 146'. Cmtd w/150 sx Class 0.25 pps cellophane (177 cu ft). Circ PT BOP & csg to 600 psi/30 min, OK. Solution of the complete of	"B" neat cmt w, c 10 bbl cmt to Drilling ahead. hole clean. TOO ST&C csg, set @ silicate, 0.25 pclass "B" 50/50 es, 5 pps gilson	3% calcium chloride surface. WOC. NU BOD OH. TIH w/5 jts 7" 2: 2921'. Cmtd w/284 s: ops celloflakes, 5 pp poz w/2% calcium nite (120 cu ft). Ci
Describe Proposed or Completed Operations 5-25-00 MIRU. Spud well @ 9:30 pm 5-25-00. 5-26-00 Drill to 156'. Circ hole clean. TOOH. Cosg, set @ 146'. Cmtd w/150 sx Class 0.25 pps cellophane (177 cu ft). Circ PT BOP & cosg to 600 psi/30 min, OK. Solution of the complete of the complete of the cost of the co	"B" neat cmt w, c 10 bbl cmt to Drilling ahead. hole clean. TOO ST&C csg, set @ silicate, 0.25 pClass "B" 50/50 es, 5 pps gilson OK. Drilling al	3% calcium chloride surface. WOC. NU BOD OH. TIH w/5 jts 7" 2: 2921'. Cmtd w/284 s: ops celloflakes, 5 pp poz w/2% calcium nite (120 cu ft). Ci
Describe Proposed or Completed Operations 5-25-00 MIRU. Spud well @ 9:30 pm 5-25-00. 5-26-00 Drill to 156'. Circ hole clean. TOOH. csg, set @ 146'. Cmtd w/150 sx Class 0.25 pps cellophane (177 cu ft). Circ PT BOP & csg to 600 psi/30 min, OK. 5-28-00 Drill to intermediate TD @ 2930'. Circ N-80 ST&C csg, & 65 jts 7" 20# J-55 Class "B" neat cmt w/3% sodium metal gilsonite (863 cu ft). Tail w/90 sx chloride, 2% gel, 0.25 pps celloflak 36 bbl cmt to surface. 5-29-00 WOC. PT BOP & csg to 1500 psi/30 mins, APD ROW Related	"B" neat cmt w, c 10 bbl cmt to Drilling ahead. hole clean. TOO ST&C csg, set @ silicate, 0.25 pClass "B" 50/50 es, 5 pps gilson OK. Drilling all correct.	3% calcium chloride surface. WOC. NU BOD NU BOD NU TIH w/5 jts 7" 2: 2921'. Cmtd w/284 stops celloflakes, 5 pp poz w/2% calcium aite (120 cu ft). Citaead.
Describe Proposed or Completed Operations 5-25-00 MIRU. Spud well @ 9:30 pm 5-25-00. 5-26-00 Drill to 156'. Circ hole clean. TOOH. csg, set @ 146'. Cmtd w/150 sx Class 0.25 pps cellophane (177 cu ft). Circ PT BOP & csg to 600 psi/30 min, OK. 5-28-00 Drill to intermediate TD @ 2930'. Circ N-80 ST&C csg, & 65 jts 7" 20# J-55 Class "B" neat cmt w/3% sodium metal gilsonite (863 cu ft). Tail w/90 sx chloride, 2% gel, 0.25 pps celloflak 36 bbl cmt to surface. 5-29-00 WOC. PT BOP & csg to 1500 psi/30 mins, APD ROW Related	"B" neat cmt w, c 10 bbl cmt to Drilling ahead. hole clean. TOO ST&C csg, set @ silicate, 0.25 pClass "B" 50/50 es, 5 pps gilson OK. Drilling all correct.	3% calcium chloride surface. WOC. NU BOD OH. TIH w/5 jts 7" 2: 2921'. Cmtd w/284 s: ops celloflakes, 5 pp poz w/2% calcium nite (120 cu ft). Ci
Describe Proposed or Completed Operations 5-25-00 MIRU. Spud well @ 9:30 pm 5-25-00. 5-26-00 Drill to 156'. Circ hole clean. TOOH. csg, set @ 146'. Cmtd w/150 sx Class 0.25 pps cellophane (177 cu ft). Circ PT BOP & csg to 600 psi/30 min, OK. 5-28-00 Drill to intermediate TD @ 2930'. Circ N-80 ST&C csg, & 65 jts 7" 20# J-55 Class "B" neat cmt w/3% sodium metal gilsonite (863 cu ft). Tail w/90 sx chloride, 2% gel, 0.25 pps celloflak 36 bbl cmt to surface. 5-29-00 WOC. PT BOP & csg to 1500 psi/30 mins, APD ROW Related 14. I hereby certify that the foregoing is true and Signed APD ROW Federal or State Office use)	"B" neat cmt w, c 10 bbl cmt to Drilling ahead. hole clean. TOO ST&C csg, set @ silicate, 0.25 pClass "B" 50/50 es, 5 pps gilson OK. Drilling all correct.	3% calcium chloride surface. WOC. NU BO. OH. TIH w/5 jts 7" 2. 2921'. Cmtd w/284 s. Ops celloflakes, 5 p. poz w/2% calcium aite (120 cu ft). Cinead.
Describe Proposed or Completed Operations 5-25-00 MIRU. Spud well @ 9:30 pm 5-25-00. 5-26-00 Drill to 156'. Circ hole clean. TOOH. csg, set @ 146'. Cmtd w/150 sx Class 0.25 pps cellophane (177 cu ft). Circ PT BOP & csg to 600 psi/30 min, OK. 15-28-00 Drill to intermediate TD @ 2930'. Circ N-80 ST&C csg, & 65 jts 7" 20# J-55 Class "B" neat cmt w/3% sodium metal gilsonite (863 cu ft). Tail w/90 sx chloride, 2% gel, 0.25 pps celloflak 36 bbl cmt to surface. 5-29-00 WOC. PT BOP & csg to 1500 psi/30 mins, APD ROW Related Title Regulato	"B" neat cmt w, c 10 bbl cmt to Drilling ahead. hole clean. TOO ST&C csg, set @ silicate, 0.25 pClass "B" 50/50 es, 5 pps gilson OK. Drilling all correct. Ty Supervisor A Date	3% calcium chloride surface. WOC. NU BO OH. TIH w/5 jts 7" 2 2921'. Cmtd w/284 stops celloflakes, 5 ptopoz w/2% calcium aite (120 cu ft). Cinead. CEPSUSD/60R RECOR