Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB NO/1004-0135
Expires: November 30, 2000

5. Lease Serial No.

abandoned well. Use Form 3160-3 (APD) for such proposes: SUBMIT IN TRIPLICATE - Other instructions on reverse side CCIVED 7. If USAN DIV San DIV	Unit or CA/Agreement, Name and/or No. Juan 32-8 Unit Name and No. Juan #257
SUBMIT IN TRIPLICATE - Other instructions on reverse side CEIVED 1. Type of Well San	Juan 32-8 Unit
	oll Name and No.
Oil Well X Gas Well Other 8. We	
	2-8 Unit #257
2. Name of Operator SJ 32	
	I Well No.
FF0F III C4 NDI 2004 F	15-30258 ield and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	E 113 LO. 3
	1 Fruitland Coal Ounty or Parish, State
55575H 25, 152H, 16H	Juan, NM
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OT	
TYPE OF SUBMISSION TYPE OF ACTION	
Notice of Intent Acidize Deepen Production (Start/R.	
X Subsequent Report Alter Casing Fracture Treat Reclamation	Well Integrity
Casing Repair New Construction Recomplete	X Other
Final Abandonment Notice Change Plans Plug and Abandon Temporarily Aband	on NTL-FRA-90-1
Convert to Injection Plug Back Water Disposal	
following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new intervitesting has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have the determined that the final site is ready for final inspection.) Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1. Date: 11/24/00 Time Started: 0130 hrs Time Completed: 0245 hrs. Hole: 8-3/4" Casing Size: 7", 20#, J-55 New; Casing Set 3031' ft. Turbo Centralizers at 3020', 2983', 2942', 2855', 2769' 2683', 216', Spring Type Centralizers 1860', 1816', 1773', Mud Flush 10 bbls, Spacer 10 Fresh Water w/red dye. Stage 1: Lead Slurry: 370 (879.3cf) Type 3 cement 35:65 POZ w/5#/sx Gilsonite, ½#/sx Cello-flake 6% gel, 10#/sx CSE, 3% KCl, 0.4% FL-25, 0.02#/sx Static Free @ 2.37 yield. Tail Slurry: 50 sx (70 cf) Type 3 cement w/14/#/sx Cello-flake, 1% CaCl2, @ 1.4 yield. Volume Cement Circulated 8 bbls/sacks Displaced Plug with 121 bbls fresh water and the power of the power o	een completed, and the operator has
14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) Title	
Patsy Clugston Sr. Regulatory/Pror	ation Clerk
THIS SPACE FOR FEDERAL OR STATE OFFICE USE	ACCEPTED FOR REC 30
	PD+C 2 2 2000
Approved by	
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	FARMINGTON FIELD OF. JE