

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE
(See other instructions on reverse side)

FOR APPROVED
OMB NO. 1004-0137
Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐		5. LEASE DESIGNATION AND SERIAL NO. SF-078115	
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other ☐		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
2. NAME OF OPERATOR BURLINGTON RESOURCES OIL & GAS COMPANY		7. UNIT AGREEMENT NAME	
3. ADDRESS AND TELEPHONE NO. PO BOX 4289, Farmington, NM 87499 (505) 326-9700		8. FARM OR LEASE NAME, WELL NO. Grenier #6B	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface 1165'FSL, 665'FWL At top prod. interval reported below At total depth		9. API WELL NO. 30-045-30465	
10. FIELD AND POOL, OR WILDCAT Blanco Mesaverde		11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA Sec.20, T-31-N, R-11-W	
14. PERMIT NO.		DATE ISSUED	
12. COUNTY OR PARISH San Juan		13. STATE New Mexico	
15. DATE SPUNDED 2-2-01	16. DATE T.D. REACHED 2-7-01	17. DATE COMPL. (Ready to prod.) 2-25-01	18. ELEVATIONS (OF, RKB, RT, BR, ETC.)* 6039'GL, 6054'KB
19. ELEV. CASINGHEAD	20. TOTAL DEPTH, MD & TVD 5254'		
21. PLUG, BACK T.D., MD & TVD 5249'	22. IF MULTIPLE COMPL., HOW MANY*	23. INTERVALS DRILLED BY	24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)* 3391-5172' Mesaverde
25. WAS DIRECTIONAL SURVEY MADE No			26. TYPE ELECTRIC AND OTHER LOGS RUN CBL-GR-CCL
27. WAS WELL CORED No			
28. CASING RECORD (Report all strings set in well)			
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE
9 5/8	32.3#	221'	12 1/4
7	20#	2976'	8 3/4
29. LINER RECORD			
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*
4 1/2	2866'	5253'	365 cu. ft.
30. TUBING RECORD			
SIZE	DEPTH SET (MD)	PACKER SET (MD)	
2 3/8	4959'	SN @ 4953'	
31. PERFORATION RECORD (Interval, size and number)			
3391, 3393, 3484, 3486, 3488, 3654, 3656, 3658, 3660, 3662, 3677, 3679, 3692, 3694, 3696, 3750, 3752, 3754, 3756, 3758, 3764, 3766, 3768, 3770, 3772, 3836, 3838, 3840, 3842, 3844, 3858, 3860, 3880, 3882, 3884, 3886, 3888, 3908, 3910, 3912, 3914, 3919, 3938, 3940, 3942, 4526, 4532, 4536, 4539, 4565, 4568, 4580, 4584, 4588, 4604, 4669, 4677, 4712, 4715, 4722,			
32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.			
DEPTH INTERVAL (MD)		AMOUNT AND KIND OF MATERIAL USED	
3391-3942'		606 bbl 20# lnr gel, 200,000# 20/40 AZ sd, 1141 Mscf N2.	
4526-4761'		1615 bbl slk wtr, 75,000# 20/40 AZ sand.	
4811-5172'		2128 bbl slk wtr, 100,000# 20/40 AZ sand.	
33. PRODUCTION			
DATE FIRST PRODUCTION	PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)		WELL STATUS (Producing or shut-in)
	Flowing		SI
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD
2-25-01			
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL-BBL
SI 575	SI 575		615 Pitot gauge
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) To be sold			
35. LIST OF ATTACHMENTS None			
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records			
SIGNED <i>[Signature]</i>		TITLE Regulatory Supervisor	
FARMINGTON FIELD OFFICE		BY <i>[Signature]</i>	
DATE 3-5-01			

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	GEOLOGIC MARKERS		
				NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Ojo Alamo	945'	999'	White, cr-gr ss.	Ojo Alamo	945'	
Kirtland	999'	1944'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	999'	
Fruitland	1944'	2558'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	1944'	
Pictured Cliffs	2558'	2743'	Bn-Gry, fine grn, tight ss.	Pictured Cliffs	2558'	
Lewis	2743'	3302'	Shale w/siltstone stringers	Lewis	2743'	
Huerfanito Bentonite*	3302'	3650'	White, waxy chalky bentonite	Huerfanito Bent	3302'	
Chacra	3650'	4099'	Gry fn grn silty, glauconitic sd stone w/drk gry shale	Chacra	3650'	
Cliff House	4099'	4347'	ss. Gry, fine-grn, dense sil ss.	Cliffhouse	4099'	
Menefee	4347'	4869'	Med-dark gry, fine gr ss, carb sh & coal	Menefee	4347'	
Point Lookout	4869'	5254'	Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation	Point Lookout	4869'	
				<u>Perfs Continued:</u> 4726, 4732, 4742, 4747, 4757, 4761, 4811, 4820, 4833, 4840, 4848, 4860, 4871, 4882, 4892, 4914, 4922, 4938, 4948, 4956, 4974, 5004, 5047, 5058, 5081, 5090, 5107, 5114, 5130, 5172.		

* Huerfanito Bentonite is the legal top of Mesaverde in New Mexico (north of Chacra line).